

iiyama ProLite TF1633MSC-B1 - LED monitor

15.6" - open frame - touchscreen - 1920 x 1080 Full HD (1080p) @ 60 Hz - IPS - 450 cd/m² - 1000:1 - 5 ms - HDMI - DisplayPort - speakers - black - matte finish

Group	Flat Screens
Manufacturer	iiyama
Manufacturer item no.	TF1633MSC-B1
EAN/UPC	4948570122530



Description

iiyama ProLite TF1633MSC-B1 - LED monitor - 15.6" - open frame - touchscreen - 1920 x 1080 Full HD (1080p) @ 60 Hz - IPS - 450 cd/m² - 1000:1 - 5 ms - HDMI, DisplayPort - speakers - black, matte finish

Main features

Product Description	iiyama ProLite TF1633MSC-B1 - LED monitor - Full HD (1080p) - 15.6"
Device Type	LED-backlit LCD monitor - 15.6" - touchscreen
Energy Class	Class C
Features	Touch-screen, USB 2.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.179 mm
Brightness	450 cd/m ²
Contrast Ratio	1000:1
Response Time	5 ms (grey-to-grey)
Colour Support	16.7 million colours
Input Connectors	HDMI, DisplayPort
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black, matte finish
Dimensions (WxDxH)	38.9 cm x 4.55 cm x 24.65 cm
Weight	2 kg
Compliant Standards	Plug and Play, DDC-2B, RoHS, WEEE, REACH, TUV Bauart, ERP, EAC, REACH SvHC, UKCA, IP54 front

Extended details

General

Display Type	LED-backlit LCD monitor / TFT active matrix
--------------	---

Energy Class	Class C
Diagonal Size	15.6"
Built-in Devices	USB 2.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.179 mm
Brightness	450 cd/m ²
Brightness w/touchscreen	385 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	5 ms (grey-to-grey)
Horizontal Refresh Rate	30 - 68 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Backlight Technology	LED backlight
OSD Languages	Czech, English, German, French, Italian, Portuguese, Polish, Russian, Spanish, Dutch, Japanese, Chinese
Features	HDCP, fanless cooling, edge-to-edge glass, OSD lock, scratch-resistant, Projected Capacitive Touch (P-CAP) technology, glove touch mode, Blue Light Reducer Function
Colour	Black, matte finish
Dimensions (WxDxH)	38.9 cm x 4.55 cm x 24.65 cm
Weight	2 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Input
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
	Connectivity
Interfaces	DisplayPort HDMI 2 x USB 2.0 downstream (Type A) USB 2.0 upstream (Type B)
	Mechanical
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately), VESA interface support, 85% light transmittance, cable management system
Cables Included	1 x HDMI cable 1 x USB cable 1 x power cable
Compliant Standards	Plug and Play, DDC-2B, RoHS, WEEE, REACH, TUV Bauart, ERP, EAC, REACH SvHC, UKCA, IP54 front
Security Slot Type	Kensington security slot

	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (Typical)	12 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.3 Watt
	Dimensions & Weight (Shipping)
Shipping Width	47.5 cm
Shipping Depth	16.9 cm
Shipping Height	34.3 cm
Shipping Weight	3.9 kg
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.