

Iiyama ProLite XU2792UHSU-B6 - LED monitor

27" - 3840 x 2160 4K @ 60 Hz - IPS - 350 cd/m² - 1300:1 - 4 ms - HDMI - DisplayPort - speakers - matte black

Group	Flat Screens
Manufacturer	Iiyama
Manufacturer item no.	XU2792UHSU-B6
EAN/UPC	4948570123797



Description

Iiyama ProLite XU2792UHSU-B6 - LED monitor - 27" - 3840 x 2160 4K @ 60 Hz - IPS - 350 cd/m² - 1300:1 - 4 ms - HDMI, DisplayPort - speakers - matte black

Main features

Product Description	Iiyama ProLite XU2792UHSU-B6 - LED monitor - 4K - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class F
Power Consumption (On mode)	26 W
Features	USB 3.2 Gen 1 hub, USB PD 15 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	4K 3840 x 2160 at 60 Hz
Pixel Pitch	0.155 mm
Brightness	350 cd/m²
Contrast Ratio	1300:1 / 80000000:1 (dynamic)
Response Time	4 ms (grey-to-grey)
Colour Gamut	100% sRGB, 72% NTSC
Input Connectors	HDMI, DisplayPort
Display Position Adjustments	Tilt
Screen Coating	Matte
Voltage	AC 100-240 V (50/60 Hz)
Colour	Matte black
Dimensions (WxDxH)	61.45 cm x 19 cm x 43.95 cm
Weight	4.7 kg
Compliant Standards	TUV GS, VCCI, DDC-2B, RoHS, WEEE, PSE Mark, REACH, ERP, EAC, UKCA

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class F
Diagonal Size	27"
Built-in Devices	USB 3.2 Gen 1 hub
USB Power Delivery	15 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	4K 3840 x 2160 at 60 Hz
Pixel Pitch	0.155 mm
Brightness	350 cd/m²
Contrast Ratio	1300:1 / 80000000:1 (dynamic)
Colour Gamut	100% sRGB, 72% NTSC
Response Time	4 ms (grey-to-grey)
Horizontal Refresh Rate	30 - 140 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Screen Coating	Matte
Backlight Technology	LED backlight
OSD Languages	Czech, English, German, French, Italian, Polish, Russian, Spanish, Dutch, Japanese
Features	Eco-Mode, Advanced Contrast Ratio (ACR), Flicker Free technology, i-Style Color, Blue Light Reducer Function, 3-sided borderless
Colour	Matte black
Dimensions (WxDxH)	61.45 cm x 19 cm x 43.95 cm
Weight	4.7 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Connectivity
Interfaces	HDMI DisplayPort 1.2 3 x USB 3.2 Gen 1 USB-C with Power Delivery (power up to 15W)
	Mechanical
Display Position Adjustments	Tilt
Tilt Angle	-4/+20
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately), integrated cable management, VESA interface support

Cables Included	1 x HDMI cable 1 x DisplayPort cable 1 x USB cable
Compliant Standards	TUV GS, VCCI, DDC-2B, RoHS, WEEE, PSE Mark, REACH, ERP, EAC, UKCA
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	26 W
Power Consumption SDR (On mode)	26 kWh/1000h
Power Consumption (Typical)	34 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.3 Watt
Dimensions & Weight (Shipping)	
Shipping Width	68.8 cm
Shipping Depth	12.4 cm
Shipping Height	47.3 cm
Shipping Weight	7.1 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years - on-site

Technical data © 1WorldSync. Subject to technical modifications and errors.