Iiyama ProLite T2235MSC-B1 - LED monitor

22" (21.5" viewable) - touchscreen - 1920 x 1080 Full HD (1080p) @ 60 Hz - VA - 3000:1 - 6 ms - DVI-D - VGA - DisplayPort - speakers - black

Group	Digitale Signage
Manufacturer	Iiyama
Manufacturer item no.	T2235MSC-B1
EAN/UPC	4948570114320

Description

With 1920 x 1080 Full HD resolution and Projective Capacitive 10 point touch technology, the ProLite T2235MSC delivers seamless and accurate touch response. Featuring VA LED-backlit LCD screen technology, it offers exceptional color performance and wide viewing angles, making it an excellent choice for a vast array of demanding interactive applications. Users can benefit from its hinged stand allowing the monitor to lay down completely flat for use as a giant tablet. The T2235MSC comes equipped with several video inputs and stereo speakers delivering good quality sound. An ideal screen for Interactive Digital Signage, InStore Retail, Gaming and Interactive Presentations purposes.

Main features

Product Description	iiyama ProLite T2235MSC-B1 - LED monitor - Full HD (1080p) - 22"
Device Type	LED-backlit LCD monitor - 22" - touchscreen
Energy Class	Class F
Power Consumption (On mode)	17.2 W
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.248 mm
Contrast Ratio	3000:1 / 12000000:1 (dynamic)
Response Time	6 ms
Colour Support	16.7 million colours
Input Connectors	DVI-D, VGA, DisplayPort
Display Position Adjustments	Tilt
Colour	Black
Dimensions (WxDxH)	52.25 cm x 4.9 cm x 32.05 cm
Weight	5 kg
Compliant Standards	DDC-2B, VESA DPMS, TUV Bauart, VCCI Class B, CU-EAC

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class F
Diagonal Size	22"
Viewable Size	21.5"
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.248 mm
Brightness w/touchscreen	225 cd/m²
Contrast Ratio	3000:1 / 12000000:1 (dynamic)
Colour Support	16.7 million colours
Response Time	6 ms
Vertical Refresh Rate	55 - 75 Hz
Horizontal Refresh Rate	30 - 80 kHz
Horizontal Viewing Angle	176
Vertical Viewing Angle	176
Backlight Technology	LED backlight
Controls & Adjustments	Mute, volume, brightness, contrast, H/V position, sharpness, input select, phase, clock, blue reduction
OSD Languages	Czech, Chinese (traditional), Chinese (simplified), English, German, French, Italian, Polish, Russian, Dutch, Japanese
Features	Eco-Mode, X-Res Technology, 10-point multi-touch
Colour	Black
Dimensions (WxDxH)	52.25 cm x 4.9 cm x 32.05 cm
Weight	5 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Input
Type	Touchscreen
	Connectivity
Interfaces	VGA ¦ DVI-D ¦ DisplayPort ¦ USB ¦ Audio line-in
	Mechanical
Display Position Adjustments	Tilt
Tilt Angle	-15/+70
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately)
Cables Included	1 x audio cable ¦ 1 x DVI cable ¦ 1 x USB cable
Compliant Standards	DDC-2B, VESA DPMS, TUV Bauart, VCCI Class B, CU-EAC
Security Slot Type	Kensington security slot
	Power
Voltage Required	AC 120/230 V (50/60 Hz)

Power Consumption (On mode)	17.2 W
Power Consumption SDR (On mode)	17.2 kWh/1000h
Power Consumption (Typical)	21 Watt
Power Consumption Stand by	0.5 Watt
	Software / System Requirements
OS Required	Linux, Microsoft Windows Vista / 7 / 8, Windows 10
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years

Technical data © CNET Content Solutions. Subject to technical modifications and errors.