Iiyama ProLite TF4339MSC-B1AG

43" Diagonal Class (42.5" viewable) LED-backlit LCD display - interactive digital signage - with touchscreen (multi touch) - 1080p (Full HD) 1920 x 1080 - matte black

Group	Flat Screens
Manufacturer	Iiyama
Manufacturer item no.	TF4339MSC-B1AG
EAN/UPC	4948570118045

Description

Touch-through-glass technology, ensuring a seamless and accurate touch response for true kiosk integration or behind-glass-retail applications. The vibrant, Full HD open-frame monitor with slim borders is the ideal display solution for interactive shop windows, education, kiosks and in-store communications. It can be installed in landscape, portrait and face-up orientation for maximum flexibility and accessibility. With its AMVA3 LED panel, it offers exceptional color performance, high contrast and wide viewing angles. Featuring a metal housing with a ball-drop-proof, scratch-resistant, edge-to-edge glass, this display can be installed in the demanding environments and built in different setups as a result of its open-frame side mounting holes.

Main features

Product Description	iiyama ProLite TF4339MSC-B1AG 43" Class (42.5" viewable) LED-backlit LCD display - Full HD
Product Type	LED-backlit LCD flat panel display with touchscreen (multi touch)
Diagonal Class	43"
Diagonal Size	42.5"
Commercial Use	Yes - interactive digital signage
Colour	Matte black
Resolution	1920 x 1080
Display Format	1080p (Full HD)
Frame Rate & Enhancement Technology	60 Hz Frame Rate
Video Interface	HDMI
HDMI Ports Qty	2 ports
Connectivity	LAN
PC Interface	VGA (HD-15), HDMI, DisplayPort
Technology	AMVA3
LCD Backlight Technology	LED backlight

Image Aspect Ratio	16:9
TV Tuner	No tuner
Speaker System	2 speakers
USB	Yes
Included Accessories	Cable cover
Voltage	AC 120/230 V (50/60 Hz)
Energy Class	Class G
Power Consumption Operational	60 Watt
Power Consumption (On mode)	55.6 W
Power Consumption Stand by	1.5 Watt
Dimensions (WxDxH) - without stand	98.5 cm x 6.8 cm x 57.75 cm
Weight	23 kg

Extended details

	General
Product Type	LED-backlit LCD flat panel display
Energy Class	Class G
Power Consumption Operational	60 Watt
Power Consumption (On mode)	55.6 W
Power Consumption SDR (On mode)	55.6 kWh/1000h
Diagonal Class	43"
Diagonal Size	42.5"
Commercial Use	Yes - interactive digital signage
Combined With	Touchscreen (multi touch)
TV Tuner	No tuner
TV Tuner Presence	No
Video Interface	HDMI
HDMI Ports Qty	2 ports
PC Interface	VGA (HD-15), HDMI, DisplayPort
Modes	Portrait mode, landscape mode, Face-up Mode, kiosk mode
Design	Open Frame
Dimensions	Without stand
Width	98.5 cm
Depth	6.8 cm
Height	57.75 cm
Weight	23 kg
Enclosure Colour	Matte black
	Display
LCD Display Technology	AMVA3
Pixel Pitch	0.4902 mm
Resolution	1920 x 1080

Display Format	1080p (Full HD)
Image Aspect Ratio	16:9
Frame Rate & Enhancement Technology	60 Hz Frame Rate
LCD Backlight Technology	LED backlight
Coating	Anti-glare, 7H Hard, glass coating, 3 mm glass, 16% haze
Image Contrast Ratio	4000:1
Brightness	400 cd/m²
Total Pixels	2,100,000
Viewing Angle	178 degrees
Viewing Angle (Vertical)	178 degrees
Touchpoints Qty	12
Response Time	8 ms
Display Menu Language	English, German, French, Italian, Polish, Russian, Spanish, Dutch
Operation Hours / Days	24 / 7
Features	Key lock, Palm Rejection, ball drop test proof, edge-to-edge glass, cable management, Projected Capacitive Technology (PCAP), 6 mm touch through-glass
	Stands & Mounts
Stand	Optional
Flat Panel Mount Interface	400 x 200 mm
VESA Compatibility	Yes
	Media Player
USB Port	Yes
USB Ports Qty	1
	Audio System
Speaker System	2 speakers
Output Power / Total	16 Watt
Speakers	2 x speaker - 8 Watt
	Network & Internet Multimedia
Connectivity	LAN
	Connections
Connector Type	VGA input ¦ DisplayPort input ¦ 2 x HDMI ¦ Audio input ¦ RS-232C ¦ LAN ¦ Audio output ¦ USB
	Miscellaneous
Included Accessories	Cable cover
Cables Included	DisplayPort cable ¦ USB cable ¦ HDMI cable
Compliant Standards	Plug and Play, DDC-2B, RoHS, WEEE, cULus, REACH, IP54, ERP, EAC, REACH SvHC, HDCP, UKCA
	Power
Power Device	Power supply
Input Voltage	AC 120/230 V (50/60 Hz)
Power Consumption Stand by	1.5 Watt
Power Consumption (Off Mode)	0.3 Watt

On / Off Switch	Yes
	Dimensions & Weight (Shipping)
Width (Shipping)	1.07 m
Depth (Shipping)	20 cm
Height (Shipping)	70 cm
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Technical data © CNET Content Solutions. Subject to technical modifications and errors.