



Lancom R&S Unified Firewall UF-910

Firewall - 8 ports - GigE - 1U - cloud-managed - rack-mountable

Group	Network & Security
Manufacturer	Lancom
Manufacturer item no.	55061
EAN/UPC	4044144550614

Description

LANCOM R&S Unified Firewalls offer small and medium-sized enterprises a customized complete solution for state-of-the-art security and Unified Threat Management (UTM). The next-generation Firewalls provide reliable cyber security, either stand-alone or operated via the LANCOM Management Cloud (LMC). Thanks to the setup wizard and the graphical user interface, intuitive operation and a clear overview of all secure areas in your company are possible.

Main features

Product Description	LANCOM R&S Unified Firewall UF-910 - firewall - cloud-managed
Device Type	Firewall
Form Factor	Rack-mountable - 1U
Ports Qty	8
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Performance	IPS throughput: 3.78 Gbps Firewall throughput (UDP): 60 Gbps VPN throughput (IPSec): 4.28 Gbps
Capacity	Concurrent sessions: 16700000 New sessions per second: 130000 Concurrent users: up to 500
Included Accessories	Rack mount kit
Power	AC 120/230 V (50 - 60 Hz)
Dimensions (WxDxH)	43.1 cm x 46.8 cm x 4.4 cm

Extended details

General	
Device Type	Firewall
Height (Rack Units)	1U
Built-in Devices	Status LCD
Width	43.1 cm
Depth	46.8 cm

Height	4.4 cm
Networking	
Form Factor	Rack-mountable
Ports Qty	8
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Cloud-Managed	Yes
Performance	IPS throughput: 3.78 Gbps Firewall throughput (UDP): 60 Gbps VPN throughput (IPSec): 4.28 Gbps
Capacity	Concurrent sessions: 16700000 New sessions per second: 130000 Concurrent users: up to 500
Status Indicators	Port status, power, HDD activity
Features	Metal housing
Expansion / Connectivity	
Expansion Slots	2 (total) / 2 (free) x expansion slot
Interfaces	8 x 1000Base-T - RJ-45 2 x USB 3.0 - Type A 1 x console - RJ-45
Miscellaneous	
Included Accessories	Rack mount kit
Cables Included	1 x network cable 1 x console cable
Power	
Power Device	Internal power supply
Installed Qty	2
Max Supported Qty	2
Voltage Required	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	300 Watt
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 90% (non-condensing)