

Lancom R&S Unified Firewall UF-T60

Firewall - 7 ports - GigE - DC power

Group	Network & Security
Manufacturer	Lancom
Manufacturer item no.	55004
EAN/UPC	4044144550041



Description

LANCOM R&S Unified Firewalls offer small and medium-sized enterprises a customized complete solution for advanced security and Unified Threat Management (UTM). The next-generation Firewalls provide reliable cyber security, either stand-alone or operated via the LANCOM Management Cloud (LMC). Thanks to the setup wizard and the graphical user interface, intuitive operation and a clear overview of all secure areas in your company are possible.

Main features

Product Description	LANCOM R&S Unified Firewall UF-T60 - firewall
Device Type	Firewall
Ports Qty	7
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Performance	IPS throughput: 1150 Mbps Firewall throughput: 3.7 Gbps VPN throughput (IPSec): 1200 Mbps Unified Threat Management (UTM) throughput (HTTPS traffic): 200 Mbps
Capacity	Concurrent sessions: 1000000
Power	DC 12 - 36 V
Dimensions (WxDxH)	13 cm x 15 cm x 10 cm

Extended details

	General
Device Type	Firewall
Width	13 cm
Depth	15 cm
Height	10 cm
	Networking
Ports Qty	7
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Performance	IPS throughput: 1150 Mbps Firewall throughput: 3.7 Gbps VPN throughput (IPSec): 1200 Mbps Unified Threat Management (UTM) throughput (HTTPS traffic): 200 Mbps
Capacity	Concurrent sessions: 1000000

	Expansion / Connectivity
Interfaces	5 x 1000Base-T - RJ-45 2 x 1000Base-X - SFP
	Power
Power Device	Internal power supply
Installed Qty	2
Voltage Required	DC 12 - 36 V
Power Consumption Operational	22.3 Watt
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	-20 °C
Max Operating Temperature	70 °C
Humidity Range Operating	5 - 90%

Technical data © 1WorldSync. Subject to technical modifications and errors.