

Lancom 1800EF - Router - 4-port switch

GigE

Group	Network Equipment
Manufacturer	Lancom
Manufacturer item no.	62138
EAN/UPC	4044144621383



Description

LANCOM 1800EF - Router - 4-port switch - GigE

Main features

Product Description	LANCOM 1800EF - router - desktop
Device Type	Router - 4-port switch (integrated)
Enclosure Type	Desktop
WAN Ports Qty	1
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol	NetBEUI/NetBIOS, NTP, PPPoE, SMTP, DNS
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c
Features	Firewall protection, DHCP support, NAT support, ARP support, load balancing, OCSP support, IGMP snooping, Syslog support, traffic shaping, Virtual Route Redundancy Protocol (VRRP) support, LLDP support, chassis intrusion detection, IPSec over HTTPS, IP spoofing
Power	AC 230 V
Dimensions (WxDxH)	21 cm x 14 cm x 4.5 cm
Weight	450 g

Extended details

General

Device Type	Router - 4-port switch (integrated)
Enclosure Type	Desktop
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol	NetBEUI/NetBIOS, NTP, PPPoE, SMTP, DNS
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c
Authentication Method	PAP, CHAP, X.509 certificates, MS-CHAP, MS-CHAP v.2, XAUTH authentication

Features	Firewall protection, DHCP support, NAT support, ARP support, load balancing, OCSP support, IGMP snooping, Syslog support, traffic shaping, Virtual Route Redundancy Protocol (VRRP) support, LLDP support, chassis intrusion detection, IPSec over HTTPS, IP spoofing
Compliant Standards	EN55022, EN55024, EN 60950-1
Expansion / Connectivity	
Interfaces	LAN: 4 x 10Base-T/100Base-TX/1000Base-T - RJ-45 USB 2.0: 1 x 4 pin USB Type A WAN: 1 x 10Base-T/100Base-TX/1000Base-T - RJ-45
Power	
Power Device	External power adapter
Voltage Required	AC 230 V
Power Consumption Operational	7 Watt
Miscellaneous	
Cables Included	2 x network cable - 3 m
Dimensions & Weight	
Width	21 cm
Depth	14 cm
Height	4.5 cm
Weight	450 g
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.