

Lancom GS-1208P, Unmanaged, Gigabit Ethernet (10/100/1000), Power over Ethernet (PoE), Rack mounting, 1U

16 GBit/s - 8x IEEE 802.3at PoE - 10/100/1000 Mbps - 19" 1U - 266 x 44 x 185 mm

Group	Network Equipment
Manufacturer	Lancom
Manufacturer item no.	61673
EAN/UPC	4044144616730



Description

Energy-efficient PoE switching for office environments

In offices, meeting rooms, or home offices, the LANCOM GS-1208P reliably integrates up to eight network devices such as access points, IP phones, or printers into the network. Devices that support Power over Ethernet (PoE) are supplied with power directly via the network cable in accordance with IEEE 802.3af/at – eliminating the need for additional power lines. With a switching capacity of up to 16 Gbps, the unmanaged Gigabit Ethernet switch transmits data without bottlenecks, even under full load. Its fanless, compact design ensures noiseless operation and high reliability. The robust, non-slip metal housing with an integrated power supply allows flexible installation – from the desktop to a 19" rack (rack-mount adapters included).

Main features

	General
Switch type	Unmanaged
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	8
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Power over Ethernet (PoE)	Yes
Rack mounting	Yes
Form factor	1U

Extended details

	Design
Rack mounting	Yes
Stackable	Yes
Form factor	1U
Product colour	Black
LED indicators	Yes

	Management features
Switch type	Unmanaged
	Ports & interfaces
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
	Power over Ethernet (PoE)
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Power over Ethernet plus (PoE+) ports quantity	8
Total Power over Ethernet (PoE) budget	65 W
	Network
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Auto MDI/MDI-X	Yes
	Power
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	70 W
	Data transmission
Throughput	16 Gbit/s
Store-and-forward	Yes
	Operational conditions
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90 %
	Weight & dimensions
Width	266 mm
Depth	185 mm
Height	44 mm
Weight	1 kg
	Packaging content
Manual	Yes

Rack mount kit	Yes
Performance	
Mean time between failures (MTBF)	434000 h