

Lancom GS-2326P+ - Switch - Managed



24 x 10/100/1000 (PoE+) + 2 x combo Gigabit SFP - rack-mountable - PoE+ (185 W)

Group	Network Equipment
Manufacturer	Lancom
Manufacturer item no.	61481
EAN/UPC	4044144614811

Description

The Lancom GS-2326P+ is a reliable component for modern network infrastructures for any industry or application. It networks up to 26 devices with its 24 Gigabit Ethernet ports and 2 combo ports (Ethernet or fiber-optic). This switch supplies an overall output of 185 W and is capable of powering all PoE devices connected to it without any additional power supply units or cabling. Equipped with numerous security features and a high-performance hardware platform, it is ideal for the secure and reliable networking of medium-sized networks.

Main features

Product Description	LANCOM GS-2326P+ - switch - 26 ports - Managed - rack-mountable
Device Type	Switch - 26 ports - Managed
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE+) + 2 x combo Gigabit SFP
Power Over Ethernet (PoE)	PoE+
PoE Budget	185 W
Performance	Throughput: 52 Gbps Packet filter throughput: 38.69 Mpps
Capacity	Active VLANs: 4000 Virtual interfaces (VLANs): 4096
MAC Address Table Size	8K entries
Jumbo Frame Support	9000 bytes
Routing Protocol	IGMPv2, IGMP, IGMPv3
Remote Management Protocol	SNMP 1, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, SSH, CLI
Features	Flow control, VLAN support, IGMP snooping, Syslog support, port mirroring, Weighted Round Robin (WRR) queuing, Broadcast Storm Control, IPv6 support, Multicast Storm Control, Unicast Storm Control, firmware upgradable, SNMP support, sFlow, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, Access Control List (ACL) support, Quality of Service (QoS), Jumbo Frames support, MLD snooping, LLDP support, DHCP relay, Link Aggregation Control Protocol (LACP), Class of Service (CoS), IGMP proxy,



	Duplicated Address Detection, DiffServ Code Point (DSCP) support, Internet Control Message Protocol (ICMP)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	44.2 cm x 21.2 cm x 4.4 cm
Weight	3.1 kg
Localisation	Europe

Extended details

	General
Device Type	Switch - 26 ports - Managed
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE+) + 2 x combo Gigabit SFP
Power Over Ethernet (PoE)	PoE+
PoE Budget	185 W
Performance	Throughput: 52 Gbps Packet filter throughput: 38.69 Mpps
Capacity	Active VLANs: 4000 Virtual interfaces (VLANs): 4096
MAC Address Table Size	8K entries
Jumbo Frame Support	9000 bytes
Routing Protocol	IGMPv2, IGMP, IGMPv3
Remote Management Protocol	SNMP 1, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, SSH, CLI
Encryption Algorithm	SSL
Authentication Method	Secure Shell (SSH), RADIUS, TACACS+
Features	Flow control, VLAN support, IGMP snooping, Syslog support, port mirroring, Weighted Round Robin (WRR) queuing, Broadcast Storm Control, IPv6 support, Multicast Storm Control, Unicast Storm Control, firmware upgradable, SNMP support, sFlow, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, Access Control List (ACL) support, Quality of Service (QoS), Jumbo Frames support, MLD snooping, LLDP support, DHCP relay, Link Aggregation Control Protocol (LACP), Class of Service (CoS), IGMP proxy, Duplicated Address Detection, DiffServ Code Point (DSCP) support, Internet Control Message Protocol (ICMP)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az
	Expansion / Connectivity
Interfaces	24 x 1000Base-T RJ-45 PoE+ 2 x 1000Base-X RJ-45/SFP 1 x console
	Power
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	240 Watt
	Miscellaneous

Cables Included



1 x serial cable - 1.5 m

Rack Mounting Kit	Included
Compliant Standards	FCC Class A certified, EN55022, EN55024, FCC Part 15, EN 60950-1, FCC CFR47
Localisation	Europe

Dimensions & Weight

Width	44.2 cm
Depth	21.2 cm
Height	4.4 cm
Weight	3.1 kg

Manufacturer Warranty

Service & Support	Limited warranty - 5 years
-------------------	----------------------------

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.