

Lancom GS-2426 - Switch - Managed

24 x 10/100/1000 + 2 x 1 Gigabit SFP + 2 x combo Gigabit SFP/RJ-45 - desktop - rack-mountable

Group	Network Equipment
Manufacturer	Lancom
Manufacturer item no.	61669
EAN/UPC	4044144616693



Description

LANCOM GS-2426 - Switch - Managed - 24 x 10/100/1000 + 2 x 1 Gigabit SFP + 2 x combo Gigabit SFP/RJ-45 - desktop, rack-mountable

Main features

Product Description	LANCOM GS-2426 - switch - 26 ports - Managed - rack-mountable
Device Type	Switch - 26 ports - Managed
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 + 2 x 1 Gigabit SFP + 2 x combo Gigabit SFP/RJ-45
Performance	Throughput: 52 Gbps
Capacity	Virtual interfaces (VLANs): 4096 Link aggregation ports: 16 IGMP multicast groups: 256
MAC Address Table Size	8K entries
Jumbo Frame Support	9000 bytes
Routing Protocol	IGMP, IGMPv2, IGMPv3, RSTP, MSTP, MLD
Remote Management Protocol	SNMP 1, SNMP 3, SNMP 2c, SSH, TACACS+, HTTP, HTTPS, RMON, RADIUS, ICMP, Telnet
Features	VLAN support, IGMP snooping, Syslog support, Broadcast Storm Control, IPv6 support, firmware upgradable, SNTP support, sFlow, STP support, RSTP support, MSTP support, ACL support, QoS, Jumbo Frames support, MLD snooping, LLDP support, DHCP relay, LACP, dual firmware images, VSM, IGMP proxy, 1 fan
Compliant Standards	IEEE 802.3az, IEEE 802.1x, IEEE 802.1AX, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Power	AC 100-240 V (50 - 60 Hz)
Dimensions (WxDxH)	44.2 cm x 21.2 cm x 4.4 cm
Weight	2.5 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.