



Lenovo ThinkVision P27h-20 - LED monitor

27" (27" viewable) - 2560 x 1440 WQHD - IPS - 350 cd/m² - HDMI - DisplayPort - USB-C - speakers

Group	Flat Screens
Manufacturer	Lenovo
Manufacturer item no.	61E9GAT6EU
EAN/UPC	0193638970866

Description

Engineered for tech-savvy professionals who multitask, the ThinkVision P27h-20 monitor features a four sided near-edgeless, 27" QHD display that focuses on the details and accommodates multiscreen viewing. This space-saving device puts you in control with convenient, ergonomic tilt- and swivel-angles, as well as flexible cable management for a clutter-free workspace. Plus, the USB-C one-cable solution enables connection to a range of device types, and the Smart Power function delivers unhindered performance and improved efficiency. A plethora of features including integrated speakers & an Ethernet port.

Main features

Product Description	Lenovo ThinkVision P27h-20 - LED monitor - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class F
Power Consumption (On mode)	23.5 W
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	WQHD 2560 x 1440
Brightness	350 cd/m ²
Input Connectors	HDMI, DisplayPort, USB-C
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare
Environmental Standards	TCO Certified Displays 8, TCO Certified Edge Displays
Compliant Standards	TUV Rheinland Eye Comfort Certification

Extended details

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class F

Diagonal Size	27"
Viewable Size	27"
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	WQHD 2560 x 1440
Brightness	350 cd/m ²
Vertical Refresh Rate	60 Hz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare
Backlight Technology	WLED
Features	99% sRGB colour gamut, integrated cable management, 85% DCI-P3, 99% BT.709 colour gamut, 4-side NearEdgeless, integrated phone holder

Audio

Type	Speakers - stereo
------	-------------------

Connectivity

Interfaces	HDMI DisplayPort DisplayPort output USB-C 3.1 Gen 1 USB 3.1 Gen 1 downstream with Battery Charging 3 x USB-C 3.1 Gen 1 Network
------------	--

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+35
Swivel Angle	90
Rotation Angle	90
Height Adjustment	135 mm
VESA Mounting Interface	100 x 100 mm

Miscellaneous

Features	Security lock slot (cable lock sold separately)
Cables Included	1 x USB-C to USB-C cable - 1.8 m
Compliant Standards	TUV Rheinland Eye Comfort Certification
Security Slot Type	Kensington security slot

Power

Power Consumption (On mode)	23.5 W
Power Consumption SDR (On mode)	23.5 kWh/1000h

Environmental Standards

TCO Certified	TCO Certified Displays 8, TCO Certified Edge Displays
---------------	---