



Lexmark MC3326adwe - Multifunction printer

colour - laser - 216 x 356 mm (original) - A4/Legal (media) - up to 24 ppm (copying) - up to 24 ppm (printing) - 250 sheets - 33.6 Kbps - USB 2.0 - Gigabit LAN - Wi-Fi(n) - USB 2.0 host

Group	Multifunction Printers
Manufacturer	Lexmark
Manufacturer item no.	40N9160
EAN/UPC	0734646685085

Description

The Lexmark MC3326adwe enhances your productivity with a fast color output, plus automatic scanning, copying and faxing, all in a compact, touchscreen-equipped package.

Main features

Product Description	Lexmark MC3326adwe - multifunction printer - colour
Device Type	Multifunction printer
Fax Type	Super G3 - plain paper
Printing Technology	Laser (colour)
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	600 - 2500 pages
Max Copying Speed	Up to 24 ppm (mono) / up to 24 ppm (colour)
Max Printing Speed	Up to 24 ppm (mono) / up to 24 ppm (colour)
Max Printing Resolution	Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (colour)
Max Printing Resolution Class	Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (colour)
Max Fax Transmission Speed	33.6 Kbps
Scanning	600 x 600 dpi
Display	2.8"
Original Size	216 x 356 mm (max)
Original Type	Sheets
Document Feeder Capacity	50 sheets
Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm) (max)
Media Type	Envelopes, plain paper, labels, card stock, glossy paper
Standard Media Capacity	250 sheets
Max Media Capacity	250 sheets
Bypass Feeder Capacity	1 sheet
Output Trays Capacity	100 sheets
Automatic Duplexing	Yes (printing)



Connection Availability	Yes
Interface	USB 2.0, Gigabit LAN, Wi-Fi(n), USB 2.0 host
AirPrint Enabled	Yes
Office Machine Features	Scan to e-mail, scan to FTP, scan to PC, scan to USB host
Dimensions (WxDxH)	41.12 cm x 39.41 cm x 34.44 cm
Weight	19.4 kg
Environmental Standards	ENERGY STAR Qualified

Extended details

General	
Printer Fonts	Bitmapped PCL x 2 Scalable PostScript x 91 Scalable PCL x 89
Device Type	Multifunction printer
Fax Type	Plain paper
Printing Technology	Laser - colour
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	600 - 2500 pages
Display Diagonal Size	2.8"
Display Features	Touch screen
Connection Availability	Yes
Interface	USB 2.0, Gigabit LAN, Wi-Fi(n), USB 2.0 host
AirPrint Enabled	Yes
Office Machine Features	Scan to e-mail, scan to FTP, scan to PC, scan to USB host
Memory	
Standard Memory	512 MB
Max Supported Memory	512 MB
Copying	
Max Copying Speed	Up to 24 ppm (mono) / up to 24 ppm (colour)
Max Document Enlargement	400%
Max Document Reduction	25%
Printing	
Max Printing Resolution	Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (colour)
Max Printing Resolution Class	Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (colour)
Max Printing Speed	Up to 24 ppm (mono) / up to 24 ppm (colour)
Printer Drivers / Emulations	PCL 6, PostScript 3, PCL 5, PCLm
Image Enhancement Technology	4800CQ
Automatic Duplexing	Yes
First Print Out Time B/W	10.6 sec
First Print Out Time Colour	10.6 sec
Scanning	
Scan Element	CIS
Optical Resolution	600 x 600 dpi
Fax Machine	
Compatibility	Super G3



Document & Media Handling

Max Original Size	216 x 356 mm
Original Type	Sheets
Document Feeder Capacity	50 sheets
Max Media Size	A4/Legal
Supported Media Type	Envelopes, plain paper, labels, card stock, glossy paper
Supported Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), JIS B5 (182 x 257 mm), Oficio (216 x 343 mm)
Supported Envelope Sizes	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)
Standard Media Capacity	250 sheets
Max Media Capacity	250 sheets
Bypass Feeder Capacity	1 sheet
Output Trays Capacity	100 sheets
Document & Media Handling Details	Input tray - 250 sheets weight: 60 g/m ² - 176 g/m ² Bypass tray - 1 sheet Output tray - 100 sheets ADF - 50 sheets
Speed Details	Printing: up to 24 ppm (A4) - B/W (ISO/IEC 24734) Printing: up to 24 ppm (A4) - colour (ISO/IEC 24734) Printing: up to 13 spm (A4) - B/W duplex (ISO/IEC 24734) Printing: up to 13 spm (A4) - colour duplex (ISO/IEC 24734) Copying: up to 24 ppm (A4) - B/W (ISO/IEC 24735) Copying: up to 24 ppm (A4) - colour (ISO/IEC 24735) Scanning: up to 20 spm (A4) - B/W Scanning: up to 21 spm (Letter A) - B/W Scanning: up to 20 spm (A4) - colour Scanning: up to 21 spm (Letter A) - colour

Connections

Interfaces	1 x USB 2.0 - 4 pin USB Type B 1 x Gigabit LAN - RJ-45 1 x USB 2.0 host - 4 pin USB Type A
Security Protocols & Features	SSL, LEAP, TLS, IPsec, 802.1x, TTLS, PEAP, MD5, MS-CHAPv2, SNMP 3
Operating System Support	SuSE Linux Enterprise Server 10, SuSE Linux Enterprise Server 11, MS Windows 7 (32/64 bits), Windows 8 (32/64-bits), Windows 8.1 (32/64-bits), Windows 10, SuSE Linux Enterprise Server 12, MS Windows Server 2016, Ubuntu Linux 16.04, openSUSE 42.3, openSUSE 15, Debian Linux 9.4, Debian GNU/Linux 8.11, Ubuntu Linux 18.04 LTS, Red Hat Enterprise Linux WS 7.5, Fedora 27, Fedora 28

Power

Power Consumption Operational	395 Watt
Power Consumption Standby	17 Watt
Power Consumption Sleep	1.1 Watt

Miscellaneous

First Copy Out Time B/W	13.1 sec
First Copy Out Time Colour	13.1 sec
Consumables Included	1 x Cartridge (black) - up to 750 pages ISO/IEC 19798 1 x Cartridge (cyan) - up to 500 pages ISO/IEC 19798 1 x Cartridge (magenta) - up to 500 pages ISO/IEC 19798 1 x Cartridge (yellow) - up to 500 pages ISO/IEC 19798
Compliant Standards	FCC Class B certified, GS, ICES-003 Class B, CCC, SII, UL 60950-1, KCC, IEC 60825-1, FDA, UL-AR, GOST-R, EN 60825-1, CDRH, KC, CECP, CEL, Directive

1275/2008/EC, ECMA-370, EFTA, TER, ISO 532B, IEC/EN 60950-1, CAN/CSA-C22.2 No. 60950-1, DE-UZ 205

Environmental Standards

ENERGY STAR Certified Yes

Manufacturer Warranty

Service & Support Limited warranty - 4 years with product registration

Dimensions & Weight

Width 41.12 cm

Depth 39.41 cm

Height 34.44 cm

Weight 19.4 kg

Dimensions & Weight (Shipping)

Shipping Width 44 cm

Shipping Depth 55.6 cm

Shipping Height 51.9 cm

Shipping Weight 22.7 kg

Environmental Parameters

Sound Emission 14 dBA (idle) / 50 dBA (operating)

Min Operating Temperature 10 °C

Max Operating Temperature 32 °C

Humidity Range Operating 8 - 80%