Netgear Plus GS108PEv3 - Switch

Managed - 4 x 10/100/1000 (PoE) + 4 x 10/100/1000 - desktop - wall-mountable - PoE

Group	Network Equipment
Manufacturer	Netgear
Manufacturer item no.	GS108PE-300EUS
EAN/UPC	0606449103441

Description

At NETGEAR the importance of a stable and robust network infrastructure is understood. ProSAFE products are designed to exceed the high standards required of business-class network.

Main features

Product Description	NETGEAR Plus GS108PEv3 - switch - 8 ports - Managed
Device Type	Switch - 8 ports - Managed
Subtype	Gigabit Ethernet
Ports	4 x 10/100/1000 (PoE) + 4 x 10/100/1000
Power Over Ethernet (PoE)	PoE
Performance	Bandwidth: 16 Gbps ¦ Forwarding performance: 14.88 Mpps
MAC Address Table Size	4K entries
Features	Flow control, Layer 2 switching, auto-sensing per device, auto-negotiation, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, DoS attack prevention, port mirroring, store and forward, Broadcast Storm Control, wall mountable, Quality of Service (QoS), Green Ethernet, bandwidth control
Compliant Standards	IEEE 802.3u, IEEE 802.3i, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x
Dimensions (WxDxH)	15.8 cm x 10.1 cm x 2.9 cm
Weight	0.54 kg

Extended details

	General
Device Type	Switch - 8 ports - Managed
Enclosure Type	Desktop, wall-mountable
Subtype	Gigabit Ethernet
Ports	4 x 10/100/1000 (PoE) + 4 x 10/100/1000
Power Over Ethernet (PoE)	PoE
Performance	Bandwidth: 16 Gbps ¦ Forwarding performance: 14.88 Mpps

MAC Address Table Size	4K entries
Features	Flow control, Layer 2 switching, auto-sensing per device, auto-negotiation, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, DoS attack prevention, port mirroring, store and forward, Broadcast Storm Control, wall mountable, Quality of Service (QoS), Green Ethernet, bandwidth control
Compliant Standards	IEEE 802.3u, IEEE 802.3i, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x
Status Indicators	Port status, port transmission speed, PoE, link/activity
	Expansion / Connectivity
Interfaces	4 x 1000Base-T RJ-45 ¦ 4 x 1000Base-T RJ-45 PoE
	Power
Power Device	External power adapter
	Miscellaneous
Compliant Standards	EN 60950, CB
	Software / System Requirements
Software Included	Drivers & Utilities
	Dimensions & Weight
Width	15.8 cm
Depth	10.1 cm
Height	2.9 cm
Weight	0.54 kg
	Manufacturer Warranty
Service & Support	Limited warranty - power supply - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	0 - 90% (non-condensing)
Min Storage Temperature	-20 °C
Max Storage Temperature	70 °C
Humidity Range Storage	0 - 95% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.