

Netgear Smart GS110TPv3 - Switch

smart - 8 x 10/100/1000 (PoE) + 2 x SFP - desktop - wall-mountable - PoE+ (55 W) - DC power

Group	Network Equipment
Manufacturer	Netgear
Manufacturer item no.	GS110TP-300EUS
EAN/UPC	0606449137644



Description

NETGEAR Smart GS110TPv3 - Switch - smart - 8 x 10/100/1000 (PoE) + 2 x SFP - desktop, wall-mountable - PoE+ (55 W) - DC power

Main features

Product Description	NETGEAR Smart GS110TPv3 - switch - 8 ports - smart
Device Type	Switch - 8 ports - smart
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000 (PoE) + 2 x SFP
Power Over Ethernet (PoE)	PoE+
PoE Budget	55 W
Performance	Switching fabric bandwidth: 20 Gbps Forwarding performance (64-byte packet size): 14.8 Mpps
Capacity	Packet buffer size: 512 KB ACL entries (ingress): 100 VLANs supported: 64 IPv4 routes (static): 32
MAC Address Table Size	8K entries
Jumbo Frame Support	10KB
Routing Protocol	IGMPv2, IGMP, IGMPv3, static IPv4 routing, MLDv2, MLD
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, IPv6
Features	IGMP snooping, Syslog support, DoS attack prevention, port mirroring, DiffServ support, store and forward, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, firmware upgradable, STP support, RSTP support, MSTP support, DHCP snooping, ACL support, MLD snooping, fanless, LACP, DHCP client, dual firmware images, loop prevention, tagged VLAN, cable test, LLDP-MED, protected ports, EEE, WRR, Advanced QoS, Unknown Storm Control, security slot (Kensington security lock compatible)
Compliant Standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az

Power	DC 54 V
Dimensions (WxDxH)	23.6 cm x 10.1 cm x 2.7 cm
Weight	610 g
Localisation	Europe

Technical data © 1WorldSync. Subject to technical modifications and errors.