imcopex

Netgear SOHO Gigabit Ethernet Switch GS316

Switch - unmanaged - 16 x 10/100/1000 - desktop - wall-mountable

Group	Network Equipment
Manufacturer	Netgear
Manufacturer item no.	GS316-100PES
EAN/UPC	0606449113136

Description

The NETGEAR SOHO Ethernet Unmanaged Switches provide easy and affordable network connectivity to small offices and home offices. They are easy to use, reliable, and rugged with metal enclosures. With these Plug-and-Play switches, you can quickly and easily expand your network connections to multiple devices, with no configuration required.

Main features

Product Description	NETGEAR SOHO Gigabit Ethernet Switch GS316 - switch - 16 ports - unmanaged
Device Type	Switch - 16 ports - unmanaged
Subtype	Gigabit Ethernet
Ports	16 x 10/100/1000
Performance	Bandwidth: 32 Gbps ¦ Throughput (64-byte packet size): 1448000 packets per second ¦ Latency (64-byte packets): 3.9 µs
MAC Address Table Size	16K entries
Jumbo Frame Support	9216 bytes
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), Quality of Service (QoS), Green Ethernet, Energy Efficient Ethernet, security lock slot (cable lock sold separately)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
Dimensions (WxDxH)	28.6 cm x 10.1 cm x 2.6 cm
Weight	840 g

Extended details

	General
Device Type	Switch - 16 ports - unmanaged
Enclosure Type	Desktop, wall-mountable
Subtype	Gigabit Ethernet

Ports	16 x 10/100/1000
Performance	Bandwidth: 32 Gbps ¦ Throughput (64-byte packet size): 1448000 packets per second ¦ Latency (64-byte packets): 3.9 µs
MAC Address Table Size	16K entries
Jumbo Frame Support	9216 bytes
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), Quality of Service (QoS), Green Ethernet, Energy Efficient Ethernet, security lock slot (cable lock sold separately)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
Status Indicators	Port transmission speed, power, link/activity
	Expansion / Connectivity
Interfaces	16 x 1000Base-T RJ-45
	Power
Power Device	External power adapter
Power Consumption Operational	8.4 Watt
	Miscellaneous
Compliant Standards	CB, CCC, FCC Part 15 A
	Dimensions & Weight
Width	28.6 cm
Depth	10.1 cm
Height	2.6 cm
Weight	840 g
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-20 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95%

Technical data © CNET Content Solutions. Subject to technical modifications and errors.