



## Netgear GS605v4 - Switch - unmanaged

5 x 10/100/1000 - desktop

|                       |                   |
|-----------------------|-------------------|
| Group                 | Network Equipment |
| Manufacturer          | Netgear           |
| Manufacturer item no. | GS605-400PES      |
| EAN/UPC               | 0606449105827     |

### Description

The NETGEAR SOHO Ethernet unmanaged switches provide easy and affordable network connectivity to home and small offices. They are easy to use and reliable. With these Plug-and-Play switches, you can expand your network connections to multiple devices instantly. This series of switches also implement various energy saving technologies, helping you save power and money.

### Main features

|                        |   |
|------------------------|---|
| Product Description    | NETGEAR GS605v4 - switch - 5 ports - unmanaged  |
| Device Type            | Switch - 5 ports - unmanaged  |
| Subtype                | Gigabit Ethernet  |
| Ports                  | 5 x 10/100/1000   |
| MAC Address Table Size | 2K entries  |
| Features               | Auto-negotiation, auto-uplink (auto MDI/MDI-X), fanless, 128KB packet buffer, Energy Efficient Ethernet |
| Dimensions (WxDxH)     | 14.7 cm x 9.7 cm x 2.8 cm   |
| Weight                 | 200 g   |
| Localisation           | Europe  |

### Extended details

#### General

|                        |   |
|------------------------|---|
| Device Type            | Switch - 5 ports - unmanaged  |
| Enclosure Type         | Desktop   |
| Subtype                | Gigabit Ethernet  |
| Ports                  | 5 x 10/100/1000   |
| MAC Address Table Size | 2K entries  |
| Features               | Auto-negotiation, auto-uplink (auto MDI/MDI-X), fanless, 128KB packet buffer, Energy Efficient Ethernet |
| Status Indicators      | Port transmission speed, power, link/activity   |



|                               |   |
|-------------------------------|---|
|                               | <b>Expansion / Connectivity</b>                         |
| Interfaces                    | 5 x 1000Base-T RJ-45                                    |
|                               | <b>Power</b>  |
| Power Device                  | External power adapter                                  |
| Power Consumption Operational | 3.7 Watt  |
|                               | <b>Miscellaneous</b>                                    |
| MTBF                          | 6,421,778 hours   |
| Compliant Standards           | FCC Class B certified, CB, C-Tick Class B, VCCI Class B |
| Localisation                  | Europe  |
|                               | <b>Dimensions &amp; Weight</b>                          |
| Width                         | 14.7 cm   |
| Depth                         | 9.7 cm  |
| Height                        | 2.8 cm  |
| Weight                        | 200 g   |
|                               | <b>Manufacturer Warranty</b>                            |
| Service & Support             | Limited warranty - 2 years                              |
|                               | <b>Environmental Parameters</b>                         |
| Min Operating Temperature     | 0 °C  |
| Max Operating Temperature     | 40 °C   |
| Humidity Range Operating      | 10 - 90% (non-condensing)                               |

Technical data © CNET Content Solutions. Subject to technical modifications and errors.