

Netgear Smart GS728TXP - V3 - switch

L3 Lite - smart - 24 x 10/100/1000 (PoE+) + 4 x SFP+ - desktop - rack-mountable - PoE+ (190 W)

Group	Network Equipment
Manufacturer	Netgear
Manufacturer item no.	GS728TXP-300EUS
EAN/UPC	0606449171068



Description

NETGEAR Smart GS728TXP - V3 - switch - L3 Lite - smart - 24 x 10/100/1000 (PoE+) + 4 x SFP+ - desktop, rack-mountable - PoE+ (190 W)

Main features

Product Description	NETGEAR Smart GS728TXP - v3 - switch - 24 ports - smart - rack-mountable
Device Type	Switch - 24 ports - L3 Lite - smart
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE+) + 4 x SFP+
Power Over Ethernet (PoE)	PoE+
PoE Budget	190 W
Performance	Latency (1000 Mbps): 3.35 μ s Latency (1000 Mbps Fiber): 2.5 μ s Latency (10 Gbps Fiber): 2.124 μ s Bandwidth: 128 Gbps Forwarding rate (64-byte packets): 95.24 Mpps
Capacity	Virtual interfaces (VLANs): 256 ACLs per system: 100 ARP entries: 512 IPv4 routes (static): 32 Packet buffer size: 1.5 MB IPv6 routes (static): 32 IGMP multicast groups: 512
MAC Address Table Size	16K entries
Jumbo Frame Support	10KB
Routing Protocol	IGMP, IGMPv2, IGMPv3, MLD, MLDv2
Remote Management Protocol	IPv4, IPv6, RADIUS, DHCP, SNMP 1, SNMP 2, SNMP 3, RMON 1, RMON 2, RMON 3, RMON 9, TCP/IP, UDP, HTTPS, TFTP, HTTP, Syslog
Features	2 fans, ACL support, QoS, IGMP snooping, MLD snooping, auto video VLAN, Auto VoIP, EEE, GVRP, MAC based VLAN, Private VLAN, Protocol-based VLANs support, Voice VLAN, LLDP-MED, 802.1x authentication, VoIP support, VLAN support, CLI management, ACL

MAC based, DSCP support, dual firmware images, cloud backup, store and forward, WRR, VLAN Tagging, IP subnet-based VLANs support, GVRP, GARP, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, DHCP relay, DHCP client, DHCP snooping, ICMP IRDP, Link Aggregation, Guest VLAN, MAC lockdown, DAI, DoS protection, cable test

Compliant Standards	IEEE 802.3at, IEEE 802.3az, IEEE 802.1p, IEEE 802.1Q, IEEE 802.3ad (LACP), IEEE 802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.1x, IEEE 802.3af
Dimensions (WxDxH)	44 cm x 25.7 cm x 4.32 cm
Weight	3.78 kg
Localisation	European Union, United Kingdom

Technical data © 1WorldSync. Subject to technical modifications and errors.