

Netgear Plus XS512EM - V2 - switch

L3 - smart x 100/1000/2.5G/5G/10GBase-T x combo 10 Gigabit SFP+ - desktop - rack-mountable - for NETGEAR AGM731F - AXM764; ProSafe AGM731F - AGM734 - AXM761 - AXM762 - AXM763 - AXM764

Group	Network Equipment
Manufacturer	Netgear
Manufacturer item no.	XS512EM-200EUS
EAN/UPC	0606449174342



Description

NETGEAR Plus XS512EM - V2 - switch - L3 - smart x 100/1000/2.5G/5G/10GBase-T x combo 10 Gigabit SFP+ - desktop, rack-mountable - for NETGEAR AGM731F, AXM764; ProSafe AGM731F, AGM734, AXM761, AXM762, AXM763, AXM764

Main features

Product Description	NETGEAR Plus XS512EM - v2 - switch - 12 ports - smart - rack-mountable
Device Type	Switch - 12 ports - L3 - smart
Enclosure Type	Rack-mountable
Subtype	10 Gigabit Ethernet
Ports	X 100/1000/2.5G/5G/10GBase-T x combo 10 Gigabit SFP+
Performance	Fabric throughput: 240 Gbps Forwarding performance (64-byte packet size): 178.6 Mpps Packet buffer size: 2 MB
Capacity	VLAN entries: 64 Priority queues: 8 IGMP multicast groups: 256
MAC Address Table Size	32K entries
Jumbo Frame Support	12KB
Routing Protocol	IGMPv2, IGMP, IGMPv3
Remote Management Protocol	IPv4, IPv6
Features	VLAN support, QoS, cable test, DDos attack prevention, IGMP snooping, Link Aggregation, loop detection, port mirroring, port trunking, LACP support, Voice VLAN, VLAN management, auto camera VLAN, auto Wi-Fi VLAN, auto video VLAN, auto voice VLAN, port-based VLAN, DHCP client, port-based QoS, WRR, Auto Power Down, 2 fans
Compliant Standards	IEEE 802.3az, IEEE 802.1Q, IEEE 802.3x, IEEE 802.1p, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3bz, IEEE 802.3ae, IEEE 802.3z
Power	AC 100-240 V (50 - 60 Hz)
Dimensions (WxDxH)	33 cm x 20.8 cm x 4.3 cm
Weight	2.5 kg
Localisation	Europe, United Kingdom

Designed For

NETGEAR AGM731F, AXM764; ProSafe AGM731F, AGM734, AXM761, AXM762, AXM763, AXM764

Technical data © 1WorldSync. Subject to technical modifications and errors.