

OKI C824dn - Printer - colour

Duplex - LED - A3 - 1200 x 600 dpi - up to 26 ppm (mono) / up to 26 ppm (colour) - capacity: 400 sheets - USB 2.0 - Gigabit LAN - USB 2.0 host

Group	Printers
Manufacturer	OKI
Manufacturer item no.	47228002
EAN/UPC	5031713072072



Description

OKI C824dn - Printer - colour - Duplex - LED - A3 - 1200 x 600 dpi - up to 26 ppm (mono) / up to 26 ppm (colour) - capacity: 400 sheets - USB 2.0, Gigabit LAN, USB 2.0 host

Main features

Product Description	OKI C824dn - printer - colour - LED
Printer Type	Workgroup printer - LED - colour
Weight	40 kg
Localisation	Europe
Media Size Class	A3
Max Media Size	A3 (297 x 420 mm)
Min Media Size (Custom)	127 mm x 182 mm
Max Media Size (Custom)	297 mm x 1321 mm
Print Speed	Up to 26 ppm - B/W - A4 (210 x 297 mm) Up to 26 ppm - colour - A4 (210 x 297 mm) Up to 14 ppm - B/W - A3 (297 x 420 mm) Up to 14 ppm - colour - A3 (297 x 420 mm)
Max Resolution (B&W)	1200 x 600 dpi
Max Resolution (Colour)	1200 x 600 dpi
Automatic Duplexing	Yes
Interface	USB 2.0, Gigabit LAN, USB 2.0 host
RAM Installed (Max)	1 GB (1 GB)
Flash Memory Installed (Max)	3 GB
Language Simulation	PCL 5C, EPSON FX, IBM PPR, PCL 6, SIDM, PCL XL 3.0
Barcodes	Code 39, UCC/EAN-128, QR code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Interleaved 2 of 5, Postnet, PDF417, OCR-A, OCR-B, ZIP

Media Type	Envelopes, plain paper
Total Media Capacity	400 sheets
Media Handling	100-sheet multipurpose tray, 300-sheet input tray
Monthly Duty Cycle (max)	75000 pages
Recommended Monthly Volume	5000 pages
Networking	Print server
Power	AC 230V
System Requirements	Linux, Microsoft Windows Vista (32/64 bits), Microsoft Windows Server 2008 R2 x64 Edition, Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Windows 8 (32/64 bits), Microsoft Windows Server 2012 x64 Edition, Windows 8.1 (32/64 bits), Microsoft Windows Server 2012 R2 x64 Edition, Windows 10 (32/64 bits), Apple MacOS X 10.10 - 10.13
Dimensions (WxDxH)	44.9 cm x 55.2 cm x 36 cm

Extended details

	General
Printer Type	Workgroup printer - LED - colour
Localisation	Europe
	Printer
Print Speed	Up to 26 ppm - B/W - A4 (210 x 297 mm) Up to 26 ppm - colour - A4 (210 x 297 mm) Up to 14 ppm - B/W - A3 (297 x 420 mm) Up to 14 ppm - colour - A3 (297 x 420 mm)
Built-in Devices	Status LCD
Connectivity Technology	Wired
Interface	USB 2.0, Gigabit LAN, USB 2.0 host
Max Resolution (B&W)	1200 x 600 dpi
Max Resolution (Colour)	1200 x 600 dpi
Automatic Duplexing	Yes
First Print Out Time B/W	8.5 sec
First Print Out Time Colour	8.5 sec
Language Simulation	PCL 5C, EPSON FX, IBM PPR, PCL 6, SIDM, PCL XL 3.0
Fonts Included	87 x scalable PCL 4 x bitmapped PCL
Barcodes	Code 39, UCC/EAN-128, QR code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Interleaved 2 of 5, Postnet, PDF417, OCR-A, OCR-B, ZIP
Media Handling	100-sheet multipurpose tray, 300-sheet input tray
	RAM
RAM Installed (Max)	1 GB / 1 GB (max)
	Flash Memory

Flash Memory	3 GB
Media Handling	
Media Type	Envelopes, plain paper
Media Size Class	A3
Max Media Size	A3 (297 x 420 mm)
Min Media Size (Custom)	127 mm x 182 mm
Max Media Size (Custom)	297 mm x 1321 mm
Media Sizes	A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), A3 (297 x 420 mm), B4 (250 x 353 mm), A6 (105 x 148 mm)
Envelope Sizes	International DL (110 x 220 mm), Com-10 (105 x 241 mm), International C5 (162 x 229 mm), International C4 (229 x 324 mm)
Media Weight	64 g/m ² - 256 g/m ²
Total Media Capacity	400 sheets
Media Feeders	Input tray: 1 x automatic - 300 sheets - A3 (297 x 420 mm) weight: 64 g/m ² - 220 g/m ² Multi-purpose tray: 1 x automatic - 100 sheets weight: 64 g/m ² - 256 g/m ²
Max Media Capacity	2450 sheets
Output Trays Capacity	250 sheets
Duty Cycle	
Monthly Duty Cycle (max)	75000 pages
Recommended Monthly Volume	5000 pages
Networking	
Networking	Print server
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, IPP, HTTPS, IPPS
Security Protocols & Features	TLS, IPsec, 802.1x, SSL 3
Expansion / Connectivity	
Connections	1 x USB 2.0 - 4 pin USB Type B 1 x Gigabit LAN - RJ-45 1 x USB 2.0 host - 4 pin USB Type A
Miscellaneous	
Consumables Included	1 x toner cartridge (black) - up to 2500 pages ISO/IEC 19798 1 x toner cartridge (cyan) - up to 2500 pages ISO/IEC 19798 1 x toner cartridge (magenta) - up to 2500 pages ISO/IEC 19798 1 x toner cartridge (yellow) - up to 2500 pages ISO/IEC 19798
Power	
Power Device	Power supply - internal
Voltage Required	AC 230V
Frequency Required	50/60 Hz
Power Consumption Operational	680 Watt
Power Consumption Stand by	13 Watt
Power Consumption Sleep	1 Watt

Software / System Requirements

Software Included	OKI PrintSuperVision, OKI LPR, OKI Profile Assistant, OKI Color Correct, OKI Color Swatch Utility, OKI Network Extension, OKI Template Manager, OKI Print Job Accounting, OKI Configuration Tool, OKI Firmware Update Tool, OKI Network Card Setup
OS Required	Linux, Microsoft Windows Vista (32/64 bits), Microsoft Windows Server 2008 R2 x64 Edition, Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Windows 8 (32/64 bits), Microsoft Windows Server 2012 x64 Edition, Windows 8.1 (32/64 bits), Microsoft Windows Server 2012 R2 x64 Edition, Windows 10 (32/64 bits), Apple MacOS X 10.10 - 10.13

Environmental Standards

ENERGY STAR	Yes
-------------	-----

Manufacturer Warranty

Service & Support	Limited warranty - 3 years with product registration (within 30 days of purchase)
-------------------	---

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	32 °C
Humidity Range Operating	20 - 80%
Sound Emission (Idle)	32 dBA
Sound Emission (Operating)	54 dBA

Dimensions & Weight

Width	44.9 cm
Depth	55.2 cm
Height	36 cm
Weight	40 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.