



## OKI B432dn - Printer - B/W - Duplex

LED - A4/Legal - 1200 x 1200 dpi - up to 40 ppm - capacity: 350 sheets - USB 2.0 - Gigabit LAN

Group	Printers
Manufacturer	OKI
Manufacturer item no.	45762012
EAN/UPC	5031713063582

### Description

If you need a black & white printer that supports extremely high levels of office productivity, without straining your budget, you need the B432dn.

### Main features

Product Description	OKI B432dn - printer - B/W - LED
Printer Type	Workgroup printer - LED - B/W
Weight	12 kg
Media Size Class	A4/Legal
Max Media Size	210 x 1321 mm
Max Media Size (Custom)	210 mm x 1321 mm
Print Speed	Up to 40 ppm - B/W
Max Resolution (B&W)	1200 x 1200 dpi
Automatic Duplexing	Yes
Interface	USB 2.0, Gigabit LAN
Processor	667 MHz
RAM Installed (Max)	512 MB
Flash Memory Installed (Max)	3 GB
Language Simulation	PCL 5E, PostScript 3, PCL 6, IBM ProPrinter, XPS, PDF 1.7
Barcodes	Code 39, UCC/EAN-128, QR code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Interleaved 2 of 5, Postnet, PDF417, OCR-A, OCR-B, ZIP
Total Media Capacity	350 sheets
Media Handling	250-sheet input tray, 100-sheet bypass tray
Monthly Duty Cycle (max)	80000 pages
Recommended Monthly Volume	500 - 5000 pages
Networking	Print server
Power	AC 230V
System Requirements	Linux, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003



(32/64-bits), Apple MacOS X Lion 10.7, Apple MacOS X 10.6.8, Apple OS X 10.8 Mountain Lion, Windows 8 (32/64 bits), Microsoft Windows Server 2008 R2 (64-bits), Microsoft Windows Server 2012 x64 Edition, Windows 8.1 (32/64 bits), Microsoft Windows Server 2012 R2, Apple OS X 10.9 Mavericks, Microsoft Windows Server 2012 R2 x64 Edition

Dimensions (WxDxH) 38.7 cm x 36.4 cm x 24.5 cm

## Extended details

### General

Printer Type Workgroup printer - LED - monochrome

### Printer

Print Speed Up to 40 ppm - B/W

Built-in Devices Status LCD

Connectivity Technology Wired

Interface USB 2.0, Gigabit LAN

Max Resolution (B&W) 1200 x 1200 dpi

Automatic Duplexing Yes

First Print Out Time B/W 4.5 sec

Language Simulation PCL 5E, PostScript 3, PCL 6, IBM ProPrinter, XPS, PDF 1.7

Fonts Included 87 x PCL | 136 x PostScript | 2 x bitmapped | 1 x barcode

Barcodes Code 39, UCC/EAN-128, QR code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Interleaved 2 of 5, Postnet, PDF417, OCR-A, OCR-B, ZIP

Media Handling 250-sheet input tray, 100-sheet bypass tray

### Processor

Processor 667 MHz

### RAM

RAM Installed (Max) 512 MB

### Flash Memory

Flash Memory 3 GB

### Media Handling

Media Size Class A4/Legal

Max Media Size 210 x 1321 mm

Max Media Size (Custom) 210 mm x 1321 mm

Media Sizes ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), A6 (105 x 148 mm), Statement (139.7 x 215.9 mm)

Envelope Sizes International DL (110 x 220 mm), International C6 (114 x 162 mm), Com-10 (105 x 241 mm), International C5 (162 x 229 mm), Monarch (98.4 x 190.5 mm), Com-9 (98 x 225 mm)

Total Media Capacity 350 sheets

Media Feeders 1 x automatic - 100 sheets weight: 60 g/m<sup>2</sup> - 163 g/m<sup>2</sup> | 1 x automatic - 250 sheets weight: 60 g/m<sup>2</sup> - 105 g/m<sup>2</sup>

Max Media Capacity 880 sheets

### Duty Cycle

Monthly Duty Cycle (max) 80000 pages



Recommended Monthly Volume	500 - 5000 pages
<b>Networking</b>	
Networking	Print server
Remote Management Protocol	SNMP 1, SNMP 3, IPP, HTTP, HTTPS, IPPS
Security Protocols & Features	IPsec
<b>Expansion / Connectivity</b>	
Connections	1 x USB 2.0 - 4 pin USB Type B   1 x LAN - RJ-45
<b>Power</b>	
Power Device	Power supply - internal
Voltage Required	AC 230V
Frequency Required	50/60 Hz
Power Consumption Operational	600 Watt
Power Consumption Stand by	80 Watt
Power Consumption Sleep	1.4 Watt
<b>Software / System Requirements</b>	
OS Required	Linux, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits), Apple MacOS X Lion 10.7, Apple MacOS X 10.6.8, Apple OS X 10.8 Mountain Lion, Windows 8 (32/64 bits), Microsoft Windows Server 2008 R2 (64-bits), Microsoft Windows Server 2012 x64 Edition, Windows 8.1 (32/64 bits), Microsoft Windows Server 2012 R2, Apple OS X 10.9 Mavericks, Microsoft Windows Server 2012 R2 x64 Edition
<b>Manufacturer Warranty</b>	
Service & Support	Limited warranty - 3 years
<b>Environmental Parameters</b>	
Min Operating Temperature	10 °C
Max Operating Temperature	32 °C
Humidity Range Operating	20 - 80% (non-condensing)
Sound Emission (Idle)	30 dBA
Sound Emission (Operating)	55 dBA
<b>Dimensions &amp; Weight</b>	
Width	38.7 cm
Depth	36.4 cm
Height	24.5 cm
Weight	12 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.