



OKI B721dn - Printer - B/W - Duplex

LED - A4 - 1200 x 1200 dpi - up to 47 ppm - capacity: 630 sheets - USB 2.0 - Gigabit LAN - USB host

Group	Printers
Manufacturer	OKI
Manufacturer item no.	45487002
EAN/UPC	5031713059530

Description

The B721dn printer from OKI is designed to enhance productivity in demanding environments. This digital monochrome printer can deliver powerful, cost-effective performance, providing crisp, clear documents with high speed and low levels of user intervention. They're a powerful, reliable solution for your workgroup printing needs.

Main features

Product Description	OKI B721dn - printer - B/W - LED
Printer Type	Workgroup printer - LED - B/W
Weight	27 kg
Media Size Class	A4
Max Media Size	A4 (210 x 297 mm)
Min Media Size (Custom)	76 mm x 127 mm
Max Media Size (Custom)	216 mm x 1321 mm
Print Speed	Up to 47 ppm - B/W - A4 (210 x 297 mm)
Max Resolution (B&W)	1200 x 1200 dpi
Automatic Duplexing	Yes
Interface	USB 2.0, Gigabit LAN, USB host
Processor	800 MHz
RAM Installed (Max)	256 MB (768 MB)
Language Simulation	PCL 5E, PostScript 3, EPSON FX, IBM PPR, XPS
Barcodes	Code 39, UCC/EAN-128, QR code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Interleaved 2 of 5, Postnet, PDF417, OCR-A, OCR-B, ZIP
Media Type	Envelopes, plain paper
Total Media Capacity	630 sheets
Media Handling	100-sheet multipurpose tray, 530-sheet input tray
Monthly Duty Cycle (max)	200000 pages
Recommended Monthly Volume	20000 pages
Networking	Print server

System Requirements	UNIX, Linux, Microsoft Windows XP SP2 or later, Apple MacOS X 10.4, Apple MacOS X 10.6, Microsoft Windows Vista (32/64 bits) SP2, Apple MacOS X 10.5, Microsoft Windows Vista SP1, Microsoft Windows Server 2008 R2 x64 Edition, Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2003 (32/64-bits) SP2, Apple MacOS X Lion 10.7, Microsoft Windows Server 2008 (32/64-bits) SP1, Apple OS X 10.8 Mountain Lion, Windows 8 (32/64 bits)
Microsoft Certification	Compatible with Windows 7
Dimensions (WxDxH)	43.5 cm x 49.8 cm x 41 cm

Extended details

	General
Printer Type	Workgroup printer - LED - monochrome
	Printer
Print Speed	Up to 47 ppm - B/W - A4 (210 x 297 mm)
Built-in Devices	Status LCD
Connectivity Technology	Wired
Interface	USB 2.0, Gigabit LAN, USB host
Max Resolution (B&W)	1200 x 1200 dpi
Automatic Duplexing	Yes
PostScript Support	Standard
First Print Out Time B/W	5 sec
Language Simulation	PCL 5E, PostScript 3, EPSON FX, IBM PPR, XPS
Fonts Included	87 x scalable PCL 136 x PostScript 1 x barcode
Barcodes	Code 39, UCC/EAN-128, QR code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Interleaved 2 of 5, Postnet, PDF417, OCR-A, OCR-B, ZIP
Media Handling	100-sheet multipurpose tray, 530-sheet input tray
	Processor
Processor	800 MHz
	RAM
RAM Installed (Max)	256 MB / 768 MB (max)
	Media Handling
Media Type	Envelopes, plain paper
Media Size Class	A4
Max Media Size	A4 (210 x 297 mm)
Min Media Size (Custom)	76 mm x 127 mm
Max Media Size (Custom)	216 mm x 1321 mm
Media Sizes	A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), A6 (105 x 148 mm)
Envelope Sizes	International DL (110 x 220 mm), Com-10 (105 x 241 mm), International C5 (162 x 229 mm), Com-9 (98 x 225 mm)
Media Weight	64 g/m ² - 253 g/m ²
Total Media Capacity	630 sheets
Media Feeders	1 x automatic - 100 sheets - 216 x 1321 mm weight: 64 g/m ² - 253 g/m ² 1 x automatic - 530 sheets - A4 (210 x 297 mm) weight: 64 g/m ² - 220 g/m ²
Max Media Capacity	3160 sheets



Output Trays Capacity	500 sheets
Duty Cycle	
Monthly Duty Cycle (max)	200000 pages
Recommended Monthly Volume	20000 pages
Networking	
Networking	Print server
Remote Management Protocol	SNMP 1, SNMP 3, IPP, HTTP, HTTPS
Security Protocols & Features	Secure Print, SSL, Apple Bonjour, TLS, IPsec, 802.1x, IP filtering, MAC address filtering
Expansion / Connectivity	
Connections	1 x USB 2.0 - 4 pin USB Type B 1 x Gigabit LAN - RJ-45 1 x USB host - 4 pin USB Type A
Miscellaneous	
Consumables Included	1 x toner cartridge (black) - up to 10000 pages ISO/IEC 19752
Compatible with Windows 7	"Compatible with Windows 7" software and devices carry Microsoft's assurance that these products have passed tests for compatibility and reliability with 32-bit and 64-bit Windows 7.
Compliant Standards	GS
Power	
Power Device	Power supply - internal
Voltage Required	AC 230V
Frequency Required	50/60 Hz
Power Consumption Operational	800 Watt
Power Consumption Stand by	95 Watt
Software / System Requirements	
Software Included	OKI LPR, OKI PrintSuperVision.net, OKI Template Manager, OKI PDF Print Direct
OS Required	UNIX, Linux, Microsoft Windows XP SP2 or later, Apple MacOS X 10.4, Apple MacOS X 10.6, Microsoft Windows Vista (32/64 bits) SP2, Apple MacOS X 10.5, Microsoft Windows Vista SP1, Microsoft Windows Server 2008 R2 x64 Edition, Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2003 (32/64-bits) SP2, Apple MacOS X Lion 10.7, Microsoft Windows Server 2008 (32/64-bits) SP1, Apple OS X 10.8 Mountain Lion, Windows 8 (32/64 bits)
Environmental Standards	
ENERGY STAR	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	32 °C
Humidity Range Operating	20 - 80%
Sound Emission (Idle)	30 dBA
Sound Emission (Operating)	55 dBA
Sound Emission (Quiet Mode)	53 dBA
Dimensions & Weight	
Width	43.5 cm



Depth	49.8 cm
Height	41 cm
Weight	27 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.