

Philips 32BDL4511D - 32" Diagonal Class D-Line LED-backlit LCD display

digital signage - 1080p 1920 x 1080

Group	Digitale Signage
Manufacturer	Philips
Manufacturer item no.	32BDL4511D/00
EAN/UPC	8712581778637



Description

Make it stand out with a fast Philips D-line professional FHD display. Philips superb picture quality ensures true colors and intense contrast. You can effortlessly display content from multiple sources on a single screen.

Main features

Product Description	Philips 32BDL4511D D-Line - 32" LED-backlit LCD display - Full HD - for digital signage
Product Type	LED-backlit LCD flat panel display
Diagonal Class	32"
Commercial Use	Yes - digital signage
Resolution	1920 x 1080
Display Format	1080p
Input Video Formats	1080/60i, 480/60p, 720/60p, 1080/50i, 720/50p, 576/50p, 1080/50p, 1080/60p, 480/60i, 576/50i
Video Interface	HDMI
HDMI Ports Qty	2 ports
Connectivity	LAN
PC Interface	DVI, DisplayPort
Technology	ADS
LCD Backlight Technology	LED backlight
Image Aspect Ratio	16:9
TV Tuner	No tuner
Commercial Features	CMND management, FailOver
Picture Enhancements	Pixel Shift, Low Bright
Speaker System	2 speakers
USB	2 ports
Included Accessories	Remote control, 3 clampers
Voltage	AC 100-240 V (50/60 Hz)
Energy Class	Class G

Power Consumption Operational	36 Watt
Power Consumption Stand by	0.5 Watt
Dimensions (WxDxH) - without stand	72.65 cm x 6.51 cm x 42.54 cm
Weight	5.7 kg

Extended details

	General
Product Type	LED-backlit LCD flat panel display
Energy Class	Class G
Power Consumption (Max)	60 Watt
Power Consumption Operational	36 Watt
Power Consumption SDR (On mode)	36 kWh/1000h
Diagonal Class	32"
Commercial Use	Yes - digital signage
Series	D-Line
TV Tuner	No tuner
TV Tuner Presence	No
Video Interface	HDMI
HDMI Ports Qty	2 ports
PC Interface	DVI, DisplayPort
Modes	Portrait mode, landscape mode
Picture Enhancements	Pixel Shift, Low Bright
Dimensions	Without stand
Width	72.65 cm
Depth	6.51 cm
Height	42.54 cm
Weight	5.7 kg
	Display
LCD Display Technology	ADS
Resolution	1920 x 1080
Display Format	1080p
Image Aspect Ratio	16:9
LCD Backlight Technology	LED backlight
Coating	25% haze
Image Contrast Ratio	1200:1

Dynamic Contrast Ratio	500000:1
Brightness	400 cd/m ²
Viewing Angle	178 degrees
Viewing Angle (Vertical)	178 degrees
Response Time	8 ms
Display Menu Language	Multilingual
Backlight Life	50,000 hour(s)
Commercial Features	CMND management, FailOver
Operation Hours / Days	24 / 7
Features	OPS Slot
Stands & Mounts	
Stand	Optional
Flat Panel Mount Interface	100 x 100 mm, 200 x 200 mm
VESA Compatibility	Yes
Video Features	
Input Video Formats	1080/60i, 480/60p, 720/60p, 1080/50i, 720/50p, 576/50p, 1080/50p, 1080/60p, 480/60i, 576/50i
Supported Computer Resolutions	1024 x 768 (XGA), 640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 1024 (SXGA), 1280 x 720, 1680 x 1050 (WSXGA+), 1920 x 1080, 1440 x 900, 1600 x 900
Media Player	
Supported Video Formats	H.264, H.263, MPEG, H.265
Supported Audio Formats	AAC, HE-AAC
Supported Pictures Formats	BMP, PNG, JPEG
USB Port	Yes
USB Ports Qty	2
Remote Control	
Type	Remote control
Battery Form Factor	AAA type
Battery Included	Yes
Audio System	
Speaker System	2 speakers
Output Power / Total	20 Watt
Speakers	2 x speaker - 10 Watt
Network & Internet Multimedia	
Connectivity	LAN
Connections	

Connector Type	DisplayPort input 2 x HDMI input DVI-I input HDMI output Audio line-in Audio line-out Remote control DisplayPort output RS-232C input 2 x USB 2.0 RS-232C output Infrared output Infrared input
Miscellaneous	
Included Accessories	3 clampers
Cables Included	IR sensor cable - 1.8 m RS232 cable
Compliant Standards	FCC Class A certified, VCCI, BSMI, CB, CCC, PSB, RoHS, ETL, EMF, CECP, EAC
Power	
Power Device	Power supply
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption Stand by	0.5 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.