


Philips 65BDL3511Q - 65" Diagonal Class (64.5" viewable)

Q-Line LED-backlit LCD display - digital signage - 4K UHD (2160p)
3840 x 2160

Group	Digitale Signage
Manufacturer	Philips
Manufacturer item no.	65BDL3511Q/00
EAN/UPC	8712581778606



Description

Inform and enthrall with a Philips Q-Line Professional Ultra HD Display. This reliable solution can be up and running as quickly as you need.

Main features

Product Description	Philips 65BDL3511Q Q-Line - 65" Class (64.5" viewable) LED-backlit LCD display - 4K - for digital signage
Product Type	LED-backlit LCD flat panel display
Diagonal Class	65"
Diagonal Size	64.5"
Commercial Use	Yes - digital signage
Resolution	3840 x 2160
Display Format	4K UHD (2160p)
Input Video Formats	1080/60i, 480/60p, 720/60p, 1080/50i, 576/50p, 1080/50p, 1080/60p, 480/60i, 576/50i
Video Interface	HDMI
HDMI Ports Qty	3 ports
Connectivity	LAN
PC Interface	DVI
Technology	IPS
LCD Backlight Technology	LED backlight
Image Aspect Ratio	16:9
TV Tuner	No tuner
Commercial Features	CMND management, FailOver
Speaker System	2 speakers
USB	2 ports
Included Accessories	Remote control, 3 clampers

Voltage	AC 100-240 V (50/60 Hz)
Energy Class	Class G
Power Consumption Operational	165 Watt
Power Consumption Stand by	0.5 Watt
Dimensions (WxDxH) - without stand	146.23 cm x 6.89 cm x 83.73 cm
Weight	27.8 kg

Extended details

	General
Product Type	LED-backlit LCD flat panel display
Energy Class	Class G
Power Consumption (Max)	220 Watt
Power Consumption Operational	165 Watt
Power Consumption SDR (On mode)	160 kWh/1000h
Diagonal Class	65"
Diagonal Size	64.5"
Commercial Use	Yes - digital signage
Series	Q-Line
TV Tuner	No tuner
TV Tuner Presence	No
Video Interface	HDMI
HDMI Ports Qty	3 ports
PC Interface	DVI
Modes	Portrait mode, landscape mode, Tile Mode
Dimensions	Without stand
Width	146.23 cm
Depth	6.89 cm
Height	83.73 cm
Weight	27.8 kg
	Display
LCD Display Technology	IPS
Resolution	3840 x 2160
Display Format	4K UHD (2160p)

Image Aspect Ratio	16:9
LCD Backlight Technology	LED backlight
Coating	1% haze
Image Contrast Ratio	1200:1
Dynamic Contrast Ratio	500000:1
Brightness	400 cd/m ²
Viewing Angle	178 degrees
Viewing Angle (Vertical)	178 degrees
Response Time	8 ms
Display Menu Language	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Polish, Russian, Spanish, Turkish, Arabic, Japanese
Backlight Life	50,000 hour(s)
Commercial Features	CMND management, FailOver
Operation Hours / Days	18 / 7
	Stands & Mounts
Flat Panel Mount Interface	400 x 400 mm
VESA Compatibility	Yes
	Video Features
Input Video Formats	1080/60i, 480/60p, 720/60p, 1080/50i, 576/50p, 1080/50p, 1080/60p, 480/60i, 576/50i
Supported Computer Resolutions	1024 x 768 (XGA), 640 x 480 (VGA), 800 x 600 (SVGA), 832 x 624, 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1152 x 864, 1280 x 720, 720 x 400, 1152 x 870, 1680 x 1050 (WSXGA+), 1920 x 1080, 1440 x 900, 1280 x 800, 3840 x 2160
	Media Player
Supported Video Formats	Motion-JPEG, H.264, MPEG, WMV3
Supported Audio Formats	WMA, AAC, HE-AAC
Supported Pictures Formats	BMP, PNG, JPEG
USB Port	Yes
USB Ports Qty	2
	Remote Control
Type	Remote control
Battery Form Factor	AAA type
Battery Included	Yes
	Audio System

Speaker System	2 speakers
Output Power / Total	20 Watt
Speakers	2 x speaker - 10 Watt
Network & Internet Multimedia	
Connectivity	LAN
Connections	
Connector Type	DVI-I input 3 x HDMI input 2 x USB 2.0 Audio line-in Audio line-out Remote control RS-232C input RS-232C output Infrared output Infrared input
Miscellaneous	
Included Accessories	3 clampers
Cables Included	IR sensor cable - 1.8 m RS232 cable
Compliant Standards	FCC Class A certified, VCCI, BSMI, CB, PSB, ETL, EMF, CU
Power	
Power Device	Power supply
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption Stand by	0.5 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% RH (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.