

Philips 34B2U5600C - 5000 Series

LED monitor - curved - USB - 34" - 3440 x 1440 WQHD @ 120 Hz - VA - 300 cd/m² - 4000:1 - 4 ms - 2xHDMI - DisplayPort - USB-C - speakers - charcoal

Group	Flat Screens
Manufacturer	Philips
Manufacturer item no.	34B2U5600C/00
EAN/UPC	8712581806040



Description

Philips 34B2U5600C - 5000 Series - LED monitor - curved - USB - 34" - 3440 x 1440 WQHD @ 120 Hz - VA - 300 cd/m² - 4000:1 - 4 ms - 2xHDMI, DisplayPort, USB-C - speakers - charcoal

Main features

Product Description	Philips 34B2U5600C - 5000 Series - LED monitor - curved - 34" - HDR
Device Type	LED-backlit LCD monitor - 34"
Energy Label QR Code URL	https://eprel.ec.europa.eu/qr/1997682
Energy Class	Class F
Power Consumption (On mode)	31 W
KVM Switch	USB
Curved Screen	Yes
Features	KVM Switch, Gigabit Ethernet network adapter, USB 3.2 Gen 2/USB-C hub, USB PD 96 Watt
Panel Type	VA
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 (DisplayPort: 120 Hz, HDMI: 100 Hz, USB-C: 120 Hz)
Pixel Pitch	0.23175 mm
Brightness	300 cd/m ²
Contrast Ratio	4000:1 / 50000000:1 (dynamic)
Response Time	4 ms (grey-to-grey)
Colour Support	16.7 million colours (8-bit)
Colour Gamut	104% NTSC (CIE 1976), 120% sRGB (CIE 1931)
Input Connectors	2xHDMI, DisplayPort, USB-C
Built-in Ethernet	Yes
Display Position Adjustments	Height, swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Voltage	AC 100-240 V (50/60 Hz)

Colour	Charcoal
Dimensions (WxDxH) - with stand (highest position)	80.7 cm x 28.1 cm x 57.5 cm
Weight	10.4 kg
Environmental Standards	TCO Certified Edge Displays, TCO Certified, generation 10, for displays, ENERGY STAR Qualified
Compliant Standards	Plug and Play, ICES-003, CB, TUV Ergo, FCC, DDC/CI, RoHS, MEPS, EMF, EPA, EAC, BFR-free, HDCP 2.2, HDCP 1.4, PVC-free, Mercury-free, EAEU RoHS, UKCA, TUV Rheinland Eyesafe Display, TUV-GS, High Bit Rate 3 (HBR3)

Technical data © 1WorldSync. Subject to technical modifications and errors.