Philips 40B1U5600 - 5000 Series

LED monitor - USB - 40" (39.53" viewable) - 3440 x 1440 WQHD @ 120 Hz - IPS - 500 cd/m² - 1200:1 - DisplayHDR 400 - 4 ms - HDMI - DisplayPort - USB-C - speakers - black



Group	Flat Screens
Manufacturer	Philips
Manufacturer item no.	40B1U5600/00
EAN/UPC	8712581797478

Description

Philips 40B1U5600 - 5000 Series - LED monitor - USB - 40" (39.53" viewable) - 3440 x 1440 WQHD @ 120 Hz - IPS - 500 cd/m² - 1200:1 - DisplayHDR 400 - 4 ms - HDMI, DisplayPort, USB-C - speakers - black

Main features

Product Description	Philips 40B1U5600 - 5000 Series - LED monitor - 40" - HDR
Device Type	LED-backlit LCD monitor - 40"
Energy Class	Class F
Power Consumption (On mode)	39 W
KVM Switch	USB
Features	KVM Switch, USB 3.2 Gen 1/USB-C hub, USB PD 100 watt
Panel Type	IPS
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 (DisplayPort: 120 Hz, HDMI: 100 Hz, USB-C: 120 Hz)
Pixel Pitch	0.26925 mm
Brightness	500 cd/m²
Contrast Ratio	1200:1 / 50000000:1 (dynamic)
HDR Capable	DisplayHDR 400
Response Time	4 ms (grey-to-grey)
Colour Support	16.7 million colours (8-bit)
Colour Gamut	102% NTSC (CIE 1976), 121% sRGB (CIE 1931)
Input Connectors	HDMI, DisplayPort, USB-C
Display Position Adjustments	Height, swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black
Dimensions (WxDxH) - with stand (highest position)	94.4 cm x 28 cm x 62.8 cm

Weight	13.94 kg
Environmental Standards	TCO Certified Edge Displays, TCO Certified Displays 9, ENERGY STAR Qualified EPEAT Silver
Compliant Standards	Plug and Play, FCC Class B certified, TUV GS, ICES-003, SEMKO, CB, TUV Ergo, DDC/CI, cETLus, CU-EAC, HDCP 2.2, HDCP 1.4, USB Power Delivery 3.0, 2012/19/EU, EAEU RoHS
Manufacturer Warranty	3-year warranty

Technical data © 1WorldSync. Subject to technical modifications and errors.