Philips 49B2U5900CH - 5000 Series

LED monitor - curved - USB - 49" (48.8" viewable) - 5120 x 1440 Dual Quad HD @ 75 Hz - VA - 400 cd/m² - 3000:1 - DisplayHDR 400 - 4 ms - 2xHDMI - DisplayPort - USB-C - speakers - black



Group	Flat Screens
Manufacturer	Philips
Manufacturer item no.	49B2U5900CH/00
EAN/UPC	8712581802578

Description

Philips 49B2U5900CH - 5000 Series - LED monitor - curved - USB - 49" (48.8" viewable) - 5120 x 1440 Dual Quad HD @ 75 Hz - VA - 400 cd/m² - 3000:1 - DisplayHDR 400 - 4 ms - 2xHDMI, DisplayPort, USB-C - speakers - black

Main features

Product Description	Philips 49B2U5900CH - 5000 Series - LED monitor - curved - 49" - HDR
Device Type	LED-backlit LCD monitor - 49"
Energy Class	Class F
KVM Switch	USB
Curved Screen	Yes
Adaptive-Sync Technology	AMD Adaptive-Sync
Features	KVM Switch, Gigabit Ethernet network adapter, pop-up webcam, USB PD 100 watt
Panel Type	VA
Aspect Ratio	32:9
Native Resolution	Dual Quad HD 5120 x 1440 at 75 Hz
Pixel Pitch	0.2328 mm
Brightness	400 cd/m²
Contrast Ratio	3000:1 / 80000000:1 (dynamic)
HDR Capable	DisplayHDR 400
Response Time	4 ms (grey-to-grey)
Colour Support	1.07 billion colours
Colour Gamut	119% sRGB, 97% NTSC
Input Connectors	2xHDMI, DisplayPort, USB-C
Built-in Ethernet	Yes
Audio Input	Microphone
Built-in Webcam	5 Megapixel
Display Position Adjustments	Height, swivel, tilt

Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black
Dimensions (WxDxH) - with stand (highest position)	119.3 cm x 26.8 cm x 58.6 cm
Weight	15.21 kg
Environmental Standards	TCO Certified Edge Displays, TCO Certified Displays 9, TCO Certified, generation 10, for displays, ENERGY STAR Qualified EPEAT Silver
Compliant Standards	Plug and Play, FCC Class B certified, TUV GS, ICES-003, CB, TUV Ergo, DDC/CI, RoHS, cETLus, CU-EAC, BFR-free, HDCP 2.2, HDCP 1.4, USB Power Delivery 3.0, PVC-free, Mercury-free, EAEU RoHS, TUV Rheinland Eyesafe Display

Technical data © 1WorldSync. Subject to technical modifications and errors.