Philips 49B2U6903CH - 6000 Series

LED monitor - curved - 49" (48.8" viewable) - 5120 x 1440 SuperWide @ 100 Hz - VA - 500 cd/m² - 3000:1 - DisplayHDR 400 - 4 ms - Thunderbolt 4 - 2xHDMI - DisplayPort - speakers - silver



Group	Flat Screens
Manufacturer	Philips
Manufacturer item no.	49B2U6903CH/00
EAN/UPC	8712581804763

Description

Philips 49B2U6903CH - 6000 Series - LED monitor - curved - 49" (48.8" viewable) - 5120 x 1440 SuperWide @ 100 Hz - VA - 500 cd/m² - 3000:1 - DisplayHDR 400 - 4 ms - Thunderbolt 4, 2xHDMI, DisplayPort - speakers - silver

Main features

Product Description	Philips 49B2U6903CH - 6000 Series - LED monitor - curved - 49" - HDR
Device Type	LED-backlit LCD monitor - 49"
Energy Class	Class F
Curved Screen	Yes
Features	USB 3.2 Gen 2/USB-C hub, USB PD 100 watt
Panel Type	VA
Aspect Ratio	32:9
Native Resolution	SuperWide 5120 x 1440 (DisplayPort: 100 Hz, HDMI: 60 Hz, Thunderbolt 4: 75 Hz)
Pixel Pitch	0.2328 mm
Brightness	500 cd/m²
Contrast Ratio	3000:1 / 80000000:1 (dynamic)
HDR Capable	DisplayHDR 400
Response Time	4 ms (grey-to-grey)
Colour Support	1.07 billion colours
Colour Gamut	119% sRGB (CIE 1931), 97% NTSC (CIE 1976)
Input Connectors	Thunderbolt 4, 2xHDMI, DisplayPort
Built-in Ethernet	Yes
Audio Input	Microphone
Built-in Webcam	5 Megapixel
Display Position Adjustments	Height, swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Voltage	AC 100-240 V (50/60 Hz)

Colour	Silver
Dimensions (WxDxH) - with stand (highest position)	119.3 cm x 26.8 cm x 58.6 cm
Weight	15.45 kg
Environmental Standards	TCO Certified Edge Displays, TCO Certified Displays 9, TCO Certified, generation 10, for displays, ENERGY STAR Qualified EPEAT Silver
Compliant Standards	Plug and Play, TUV GS, ICES-003, CB, TUV Ergo, FCC, DDC/CI, RoHS, MEPS, EMF, EPA, EAC, BFR-free, HDCP 2.2, HDCP 1.4, PVC-free, Mercury-free, TUV Eyesafe Display Certification, UKCA, High Bit Rate 3 (HBR3)

Technical data © 1WorldSync. Subject to technical modifications and errors.