

Reyee Ruijie Networks RG-ES209GC-P, Managed, Gigabit Ethernet (10/100/1000), Power over Ethernet (PoE)

9-Port Gigabit Smart Cloud Managed PoE Switch

Group	Network Equipment
Manufacturer	Reyee
Manufacturer item no.	RG-ES209GC-P
EAN/UPC	6971693270404



Description

9-Port Gigabit Managed Switch with 8 PoE+ Ports
Gigabit access PoE switch fits needs in SMB network

Cost-Effective Smart Cloud Managed Switches
ES200 adopts a light-weighted Cloud management design, providing faster response to support richer features.

Automatic Loop Prevention Ensures Service Continuity
Network stays connected when network loop happens.

Cloud, Make Your Business Easy
SON, zero touch provisioning to Cloud
Configure VLANs on Ruijie Cloud APP
Monitor switch statistics at anytime anywhere
Easy maintainance, save onsite time and cost

Main features

	General
Switch type	Managed
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	9
MAC address table	4000 entries
Switching capacity	18 Gbit/s
Networking standards	IEEE 802.3af, IEEE 802.3at
DC input voltage	54 V
Power over Ethernet (PoE)	Yes

Extended details

	Management features
Switch type	Managed

Cloud-managed	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	9
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Data transmission	
MAC address table	4000 entries
Switching capacity	18 Gbit/s
Forwarding rate	13.39 Mpps
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at
10G support	No
Flow control support	Yes
Broadcast storm control	Yes
VLAN support	Yes
Number of VLANs	16
Power	
Power source	AC/DC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
DC input voltage	54 V
Power consumption (max)	130 W
Design	
Product colour	Black
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90 %
Storage relative humidity (H-H)	5 - 95 %
Weight & dimensions	
Width	202 mm
Depth	108 mm
Height	28 mm
Weight	1.3 kg

Security

Loop protection

Yes

Technical details

Warranty period

3 year(s)

Compliance certificates

CE

PerformanceMean time between failures
(MTBF)

200000 h