

RUIJIE Networks RG-ES224GC-V2, Managed, Gigabit Ethernet (10/100/1000), Rack mounting

24-Port - TCP/IP - RJ-45 - Managed - Rack-Modul

Group	Network Equipment
Manufacturer	RUIJIE
Manufacturer item no.	RG-ES224GC-V2
EAN/UPC	6971693278776



Description

Ruijie Networks RG-ES224GC-V2. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 8000 entries, Switching capacity: 48 Gbit/s. Rack mounting

Main features

	General
Switch type	Managed
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	24
MAC address table	8000 entries
Switching capacity	48 Gbit/s
Rack mounting	Yes

Extended details

	Design
Rack mounting	Yes
Product colour	Black
Reset button	Yes
LED indicators	Yes
	Management features
Switch type	Managed
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
System event log	Yes

	Ports & interfaces
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
	Power over Ethernet (PoE)
Power over Ethernet (PoE)	No
	Data transmission
MAC address table	8000 entries
Switching capacity	48 Gbit/s
Forwarding rate	35.71 Mpps
Jumbo frames support	Yes
Jumbo frames	9216
	Network
10G support	No
Port mirroring	Yes
Flow control support	Yes
Broadcast storm control	Yes
VLAN support	Yes
Number of VLANs	16
	Power
Power source	AC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	0.6 A
	Security
DHCP features	DHCP client, DHCP snooping
	Operational conditions
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90 %
Storage relative humidity (H-H)	5 - 95 %
Operating altitude	-500 - 5000 m
	Weight & dimensions
Width	440 mm
Depth	165 mm
Height	44 mm
Weight	2.8 kg

Performance

Mean time between failures
(MTBF)

200000 h