



Tenda P200 - Powerline adapter kit

HomePlug AV (HPAV) - wall-pluggable (pack of 2)

| | |
|-----------------------|-------------------|
| Group | Network Equipment |
| Manufacturer | Tenda |
| Manufacturer item no. | PL0010 |
| EAN/UPC | 6932849415025 |

Description

To build a network at home or office with minimum effort and cost, the Tenda 200 Mbps Powerline Adapter P200 is your choice. In many cases, Ethernet is just not available in places where network connectivity is needed. However, almost every room at home or office has power circuitry, which can be used to extend network connections from your broadband router. Simply plug one P200 that links to a broadband modem/router into the power outlet in one room, and plug another P200 linking to a PC or any Ethernet device in the other, you can then easily and instantly create a powerline network of up to 200 Mbps, 2x of a traditional switch or router, with the driving capability of up to 300 meters, 3x of Ethernet cable. Plus the QoS feature prioritizes your bandwidth intensive applications for lag-free experience.

Main features

| | |
|---------------------|---|
| Product Description | Tenda P200 - powerline adapter kit - wall-pluggable |
| Device Type | Powerline adapter kit |
| Packaged Quantity | 2 (specifications are for single item) |
| Enclosure Type | Wall-pluggable |
| Data Link Protocol | Ethernet, Fast Ethernet, HomePlug AV (HPAV) |
| Data Transfer Rate | 200 Mbps |
| Features | Auto-uplink (auto MDI/MDI-X) |
| Compliant Standards | IEEE 802.3, HomePlug AV |
| Power | AC 100/230 V |
| Dimensions (WxDxH) | 5.3 cm x 5.3 cm x 2.7 cm |

Extended details

General

| | |
|-------------------|--|
| Packaged Quantity | 2 (specifications are for single item) |
| Device Type | Powerline adapter kit |
| Enclosure Type | Wall-pluggable |



| | |
|---------------------------------------|---|
| Connectivity Technology | Wired |
| Data Link Protocol | Ethernet, Fast Ethernet, HomePlug AV (HPAV) |
| Data Transfer Rate | 200 Mbps |
| Encryption Algorithm | 128-bit AES |
| Features | Auto-uplink (auto MDI/MDI-X) |
| Compliant Standards | IEEE 802.3, HomePlug AV, FCC, RoHS |
| Status Indicators | Power, LAN |
| Expansion / Connectivity | |
| Interfaces | 1 x 10Base-T/100Base-TX - RJ-45 1 x HomePlug AV |
| Power | |
| Power Device | Internal power supply |
| Voltage Required | AC 100/230 V |
| Software / System Requirements | |
| Software Included | Drivers & Utilities |
| Dimensions & Weight | |
| Width | 5.3 cm |
| Depth | 5.3 cm |
| Height | 2.7 cm |
| Environmental Parameters | |
| Min Operating Temperature | 0 °C |
| Max Operating Temperature | 45 °C |
| Humidity Range Operating | 10 - 90% (non-condensing) |

Technical data © CNET Content Solutions. Subject to technical modifications and errors.