Tenda PA6 - Bridge - GigE, HomePlug AV (HPAV) 2.0

802.11b/g/n - 2.4 GHz - wall-pluggable

Group	Network Equipment
Manufacturer	Tenda
Manufacturer item no.	PA6
EAN/UPC	6932849433104

Description

With advanced HomePlug AV2 technology, PA6 provides you with stable, high-speed data transfer rates of up to 1000Mbps on the powerline and 300Mbps wireless transmission rate, and integration two Gigabit Ethernet ports for wired devices bring you ideal for HD Video Streaming, large file transfers and other high-bandwidth application.

Main features

Product Description	Tenda PA6 - bridge - 802.11b/g/n - wall-pluggable
Device Type	Bridge
Enclosure Type	Wall-pluggable
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, HomePlug AV (HPAV) 2.0
Frequency Band	2.4 GHz
Data Transfer Rate	1000 Mbps
Features	Reset button, Wi-Fi Clone button
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, HomePlug AV 2.0
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	6.3 cm x 4.2 cm x 12 cm

Extended details

	General
Device Type	Bridge
Enclosure Type	Wall-pluggable
Connectivity Technology	Wireless, wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, HomePlug AV (HPAV) 2.0
Frequency Band	2.4 GHz
Data Transfer Rate	1000 Mbps

Max Range Open Space	300 m
Features	Reset button, Wi-Fi Clone button
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, HomePlug AV 2.0, FCC, RoHS
Status Indicators	Powerline, Wi-Fi
	Expansion / Connectivity
Interfaces	2 x 10Base-T/100Base-TX/1000Base-T - RJ-45 ¦ 1 x HomePlug AV 2.0
	Aerial
Antenna Qty	2
Gain Level	2.5 dBi
	Power
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	8.9 Watt
	Miscellaneous
Cables Included	1 x network cable
	Dimensions & Weight
Width	6.3 cm
Depth	4.2 cm
Height	12 cm
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.