

TP-LINK Omada BE9300 Ceiling Mount Tri-Band Wi-Fi 7 Access Point, 2.4 GHz, 5 GHz, 6 GHz, 9300 Mbit/s, SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal,..., 2500 Mbit/s

574 Mbps (2.4 GHz) + 2880 Mbps (5 GHz) + 5760 Mbps (6 GHz) - 802.11 a/b/g/n/ac/ax/be - 1× 2.5G Ethernet - 220 × 220 × 32.5 mm



Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	EAP772-OUTDOOR
EAN/UPC	1210002602280

Description

Ultra-Thin Enterprise WiFi 7 Access Point

- Next-Gen WiFi 7
- Wi-Fi Speeds up to 9214 Mbps
- Multi-Link Operation (MLO)
- 1× 2.5G RJ45 Port
- PoE Power
- Ultra-Thin Design
- Centralized Cloud Management
- Omada Mesh Technology

Ultra-Thin Design for Flexible Deployment

The overall design of EAP772 utilizes a thinner circular arc with a groove around the top cover, fitting closer to various installation surfaces such as ceilings. The compact internal hardware layout and heat-dissipating design ensure high performance with a sharp aesthetic.

Boosted Network Security

- Secure Guest Network with up to 24 SSIDs
- Boost Your Business with SMS Login
- WPA3 for Worry-Free Open Public Networks
- Rogue AP Detection

Main features

	General
2.4 GHz	Yes
5 GHz	Yes
6 GHz	Yes
Maximum data transfer rate	9300 Mbit/s

Security algorithms	SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal
Ethernet LAN data rates	2500 Mbit/s
Product colour	White

Extended details

	Features
2.4 GHz	Yes
5 GHz	Yes
6 GHz	Yes
Maximum data transfer rate	9300 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	2880 Mbit/s
Maximum data transfer rate (6 GHz)	5760 Mbit/s
Ethernet LAN data rates	2500 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n
Number of users	380 user(s)
Bluetooth	Yes
Bluetooth version	5.2
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Airtime Fairness (ATF)	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
	Management features
Web-based management	Yes
	Security
Security algorithms	SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	24
Remote Authentication Dial-In User Service (RADIUS)	Yes
Access Control List (ACL)	Yes

	Design
Placement	Ceiling, Wall
Product colour	White
LED indicators	Yes
	Antenna
Antenna type	Internal
	Operational conditions
Operating relative humidity (H-H)	10 - 90 %
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90 %
	Packaging content
Quantity per pack	1 pc(s)
AC adapter included	No
Mounting kit	Yes
	Weight & dimensions
Width	220 mm
Depth	220 mm
Height	32.5 mm
	Ports & interfaces
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	0
	Certificates
Certification	CE, FCC, RoHS, IC