

TP-LINK EAP211-BRIDGE KIT, Network bridge, 867 Mbit/s, Wi-Fi, Ethernet LAN, White

3x Gigabit Ethernet Ports - 12V DC / 24V Passive PoE - IP65 - 1000m - IEEE 802.11 a/b/g/n/ac - 5 GHz: Up to 867 Mbps

Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	EAP211-BRIDGE KIT
EAN/UPC	4895252502541



Description

TP-Link EAP211-BRIDGE KIT. Maximum data transfer rate: 867 Mbit/s, Maximum transfer distance: 1000 m. Antenna design: Internal, Antenna type: 2x2, Antenna gain level (max): 7 dBi. Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 867 Mbit/s, Frequency band: 5 GHz. Ethernet LAN interface type: Gigabit Ethernet, Networking standards: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, Cabling technology: 10/100/1000Base-T(X). Product type: Network bridge, Mounting type: Pole, Product colour: White

Main features

	General
Maximum data transfer rate	867 Mbit/s
Maximum transfer distance	1000 m
Antenna design	Internal
Antenna type	2x2
Antenna gain level (max)	7 dBi
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
Wi-Fi	Yes
WLAN data transfer rate (max)	867 Mbit/s
Frequency band	5 GHz
Ethernet LAN	Yes
Ethernet LAN interface type	Gigabit Ethernet
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Cabling technology	10/100/1000Base-T(X)
Product type	Network bridge
Mounting type	Pole
Product colour	White

Extended details

	Features
Product type	Network bridge
Mounting type	Pole
Product colour	White
LED indicators	Power
Reset button	Yes
International Protection (IP) code	IP65
	Data transmission
Maximum data transfer rate	867 Mbit/s
Maximum transfer distance	1000 m
	Wireless LAN features
Wi-Fi	Yes
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
WLAN data transfer rate (max)	867 Mbit/s
Frequency band	5 GHz
	Network
Ethernet LAN	Yes
Ethernet LAN interface type	Gigabit Ethernet
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Cabling technology	10/100/1000Base-T(X)
	Power
Power source type	DC, PoE
DC input voltage	12 V
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) voltage	24 V
	Operational conditions
Operating temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90 %
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90 %
	Ports & interfaces
Ethernet LAN (RJ-45) ports	3
	Management features
Web-based management	Yes
	Antenna
Antenna design	Internal
Antenna type	2x2

Antenna gain level (max)	7 dBi
Weight & dimensions	
Width	224 mm
Depth	79 mm
Height	60 mm
Certificates	
Certification	CE, FCC, RoHS