

TP-LINK Tapo C460 KIT V1 - Solar-Powered Security Camera Kit

network surveillance camera - outdoor - weatherproof - colour (Day&Night) - 8 MP - 3840 x 2160 - 4K - fixed focal - audio - wireless - Wi-Fi - 2.4GHz radio - 5GHz radio - H.264 - H.265 - with Tapo A201 solar panel

Group	Network Cameras
Manufacturer	TP-LINK
Manufacturer item no.	TAPO C460 KIT
EAN/UPC	8885020624250



Description

Tapo C460 KIT V1 - Solar-Powered Security Camera Kit - network surveillance camera - outdoor - weatherproof - colour (Day&Night) - 8 MP - 3840 x 2160 - 4K - fixed focal - audio - wireless - Wi-Fi - 2.4GHz radio, 5GHz radio - H.264, H.265 - with Tapo A201 solar panel

Main features

Product Description	Tapo C460 KIT V1 - Solar-Powered Security Camera Kit - network surveillance camera - with Tapo A201 solar panel
Device Type	Network surveillance camera - fixed - outdoor - weatherproof
Bundled with	Tapo A201 solar panel
Audio	Yes: built-in microphone, built-in speaker, two-way audio capability
Camera Mount Type	Ceiling mount, wall mount
Dimensions (WxDxH)	11.46 cm x 6.48 cm x 6.48 cm
Weight	327 g
Connectivity Technology	Wireless
Camera	Colour - Day&Night
Max Resolution	3840 x 2160
Frame Rate (max)	15 frames per second
Motion Detection	Yes
Video Modes	4K
Optical Sensor Type	Progressive Scan CMOS - 1/2.7" - 8 MP
Minimum Illumination	850 lux - IR - F1.65
Focal Length Control	Fixed focal
Focal Length	3.17 mm
Lens Iris	F/1.65
Interfaces	2.4GHz radio, 5GHz radio, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

Platform	Tapo Care, Google Home
Intelligent Assistant	Alexa, Google Assistant - indirect
Cables Included	1 - USB adapter cable - 50 cm 1 - solar charging cable - 25 cm 1 - solar power extension cable - 3.8 m
Features	Starlight Technology, built-in 2 spotlights, Smart AI Detection, Person Detection, Vehicle Detection, Pet Detection, Event Notification, anti-theft protection, sound and light alarm, customised activity zone, Privacy mode, light sensor, IR-cut filter, auto-switching, reset button, Live View Control, 3D digital noise reduction (DNR), Wide Dynamic Range (WDR)
Environmental Parameters (operating)	-20 °C - 45 °C; 10 - 90% RH (non-condensing) relative humidity

Technical data © 1WorldSync. Subject to technical modifications and errors.