

TP-LINK JetStream TL-SX3206HPP V1

Switch - L2+ - Managed - desktop - rack-mountable - PoE++ (200 W)

Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	TL-SX3206HPP
EAN/UPC	6935364006617



Description

TP-Link JetStream TL-SX3206HPP V1 - Switch - L2+ - Managed - desktop, rack-mountable - PoE++ (200 W)

Main features

Product Description	TP-Link JetStream TL-SX3206HPP V1 - switch - 6 ports - Managed - rack-mountable
Device Type	Switch - 6 ports - L2+ - Managed
Enclosure Type	Rack-mountable
Subtype	10 Gigabit Ethernet
Power Over Ethernet (PoE)	PoE++
PoE Budget	200 W
Performance	Switching capacity: 120 Gbps Packet forwarding rate: 89.28 Mpps
Capacity	Priority queues: 8 Maximum aggregation groups: 8 Ports per aggregation group: 8 Layer 2 multicast filtering profiles: 256 Layer 2 multicast filtering entries per profile: 16 VLAN groups: 4000 Binding entries: 512 MAC addresses per port: up to 64 IP interfaces: 16 Static routes: 48 Static ARP entries: 128
MAC Address Table Size	32K entries
Jumbo Frame Support	9KB
Routing Protocol	IGMPv2, IGMP, IGMPv3, static IPv6 routing, MLDv2, MLD, MSTP, RSTP, STP
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, SSH, SSH-2, CLI, ICMP, DHCP, IPv4, IPv6
Features	Flow control, network monitoring, IGMP snooping, port mirroring, store and forward, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, firmware upgradable, SNTP support, STP support, QoS, DHCP server, MLD snooping, Cable Diagnostics Function, bandwidth control, DHCP relay, IP-MAC binding, MVR, port isolation, static routing, CoS, SP, tagged VLAN, GVRP, DoS, 2 fans, Time-controlled ACLs

support, Protocol-based VLANs support, system log, Link Aggregation, MIB II, dual image support, rate limit, SDN, AAA, Voice VLAN, Private VLAN, IGMP fast leave, VLAN group, proxy ARP, ZTP, EEE, BPDU Filter, WRR, HOL Blocking Prevention, loopback detection, queue scheduling support, schedule reboot, DSCP prioritisation, device discovery, DHCPv6 snooping, ACL MAC based

Compliant Standards	IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3an, IEEE 802.3at, IEEE 802.3bz, IEEE 802.3bt
Power	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH)	29.4 cm x 18 cm x 4.4 cm
System Requirements	UNIX, Apple MacOS, Novell NetWare, Linux, Microsoft Windows 98SE/2000/NT/XP/Vista/7/8/10, Microsoft Windows 11

Technical data © 1WorldSync. Subject to technical modifications and errors.