

TP-LINK JetStream TL-SG2008P - V1

switch - smart - 4 x 10/100/1000 + 4 x 10/100/1000 (PoE+) - desktop - PoE+ (62 W)

Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	SG2008P
EAN/UPC	6935364072957



Description

TP-Link JetStream TL-SG2008P - V1 - switch - smart - 4 x 10/100/1000 + 4 x 10/100/1000 (PoE+) - desktop - PoE+ (62 W)

Main features

Product Description	TP-Link JetStream TL-SG2008P - V1 - switch - 8 ports - smart
Device Type	Switch - 8 ports - smart
Subtype	Gigabit Ethernet
Ports	4 x 10/100/1000 + 4 x 10/100/1000 (PoE+)
Power Over Ethernet (PoE)	PoE+
PoE Budget	62 W
Performance	Bandwidth: 16 Gbps Packet buffer size: 4.1 Mbit
Capacity	Priority queues: 8 VLAN groups: 4000
MAC Address Table Size	8K entries
Jumbo Frame Support	9KB
Routing Protocol	IGMPv2, IGMP, IGMPv3, MLDv2, MLD, MSTP, RSTP, STP
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, SSH, SSH-2, DHCP, RSTP, RADIUS
Features	Flow control, auto-negotiation, BOOTP support, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, DoS attack prevention, port mirroring, DHCP snooping, ACL support, QoS, MLD snooping, Cable Diagnostics Function, DLDP support, fanless, LACP support, LLDP support, DHCP relay, Port Security, MIB, GVRP, NDP, port isolation, CoS, SP, 802.1x authentication, cloud managed, DSCP support, Storm Control, IP source guard, ARP inspection, Link Aggregation, scheduler, dual image support, SDN, AAA, LLDP-MED, ZTP, BPDU Filter, WRR, loopback detection, BPDU protection
Compliant Standards	IEEE 802.3u, IEEE 802.3i, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at
Dimensions (WxDxH)	20.9 cm x 12.6 cm x 2.6 cm

System Requirements

UNIX, Apple MacOS, Novell NetWare, Linux, Microsoft Windows
98SE/2000/NT/XP/Vista/7/8/10

Technical data © 1WorldSync. Subject to technical modifications and errors.