

TP-LINK JetStream TL-SX3008F V1

Switch - L2+ - Managed - rack-mountable

Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	TL-SX3008F
EAN/UPC	6935364006457



Description

TP-Link JetStream TL-SX3008F V1 - Switch - L2+ - Managed - rack-mountable

Main features

Product Description	TP-Link JetStream TL-SX3008F V1 - switch - 8 ports - Managed - rack-mountable
Device Type	Switch - 8 ports - L2+ - Managed
Enclosure Type	Rack-mountable
Subtype	10 Gigabit Ethernet
Performance	Switching capacity: 160 Gbps Packet forwarding rate: 119.04 Mbps Packet buffer size: 16 Mbit
Capacity	IP interfaces: 16 IPv4 routes (static): 48 IPv6 routes (static): 48
MAC Address Table Size	32K entries
Jumbo Frame Support	9KB
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2, CLI
Features	Network monitoring, BOOTP support, ARP support, IGMP snooping, store and forward, firmware upgradable, SNTP support, sFlow, ACL support, DHCP server, MLD snooping, bandwidth control, DLDAP support, fanless, LLDP support, DHCP relay, LACP, port based access control, MVR, port isolation, static routing, SP, SNMP support, system log, Link Aggregation, dual image support, fast leave, AAA, Static Link Aggregation, Voice VLAN, Private VLAN, VLAN group, ZTP, DoS protection, MAC based VLAN, MAB, DHCP filtering, schedule reboot, IPv4 and IPv6 dual stack, IGMP support, device discovery
Compliant Standards	IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.3ah
Power	(50/60 Hz)
Dimensions (WxDxH)	44 cm x 18 cm x 4.4 cm

Technical data © 1WorldSync. Subject to technical modifications and errors.