

TP-LINK Omada ES210GP V1 - Switch

Managed - 8 x 10/100/1000 (PoE+) + 1 x 10/100/1000 + 1 x combo Gigabit SFP/RJ-45 (uplink) - desktop - wall-mountable - PoE+ (123 W)

Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	ES210GMP
EAN/UPC	8885020620955



Description

TP-Link Omada ES210GP V1 - Switch - Managed - 8 x 10/100/1000 (PoE+) + 1 x 10/100/1000 + 1 x combo Gigabit SFP/RJ-45 (uplink) - desktop, wall-mountable - PoE+ (123 W)

Main features

Product Description	TP-Link Omada ES210GP V1 - switch - 10 ports - Managed
Device Type	Switch - 10 ports - Managed
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000 (PoE+) + 1 x 10/100/1000 + 1 x combo Gigabit SFP/RJ-45 (uplink)
Power Over Ethernet (PoE)	PoE+
PoE Budget	123 W
Performance	Switching capacity: 20 Gbps Packet forwarding rate: 14.88 Mpps Packet buffer size: 4 Mbit
Capacity	Priority queues: 8 VLAN groups: 32 VLANs supported: 4000
MAC Address Table Size	8K entries
Jumbo Frame Support	15KB
Routing Protocol	IGMP, IGMPv2, IGMPv3
Remote Management Protocol	DHCP
Features	Cloud managed, long range PoE+ up to 250m, QoS, PoE Auto Recovery, port isolation, loop prevention, VLAN support, IGMP snooping, fanless, metal housing, traffic prioritisation, SDN, reset button, security lock slot (cable lock sold separately), firmware upgradable, automatic device discovery, Cable Diagnostics Function, DHCP client, ZTP, store and forward, auto-negotiation, auto-uplink (auto MDI/MDI-X), port-based priority, DSCP based QoS, scheduler, WRR, bandwidth control, rate limit, Broadcast Storm Control, Multicast Storm Control, Unknown Storm Control, Unicast Storm Control, Static Link Aggregation, loopback detection, flow control, port mirroring, fast leave, VLAN Tagging

Compliant Standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.1p, IEEE 802.1ab (LLDP), IEEE 802.3x, IEEE 802.1Q
Dimensions (WxDxH)	20.9 cm x 12.6 cm x 2.6 cm

Technical data © 1WorldSync. Subject to technical modifications and errors.