imcopex

TP-LINK TL-SF1008P - Switch - 4 x 10/100 (PoE) + 4 x 10/100

desktop - PoE

Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	TL-SF1008P
EAN/UPC	6935364021665

Description

The TL-SF1008P 8-port 10/100M Desktop PoE Switch provides the seamless network connection. It integrates 100Mbps Fast Ethernet and 10Mbps Ethernet network capabilities.
4 of the 8 auto-negotiation RJ45 ports (port-1 to port-4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.
TL-SF1008P has the priority function which will help protect the system when the system power is overloaded.
TL-SF1008P is easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the TP-link TL-SF1008P 8-port 10/100M Desktop PoE Switch is a great selection for expanding your home or office network.

Main features

Product Description	TP-Link TL-SF1008P - switch - 8 ports
Device Type	Switch - 8 ports
Subtype	Fast Ethernet
Ports	4 x 10/100 (PoE) + 4 x 10/100
Power Over Ethernet (PoE)	PoE
MAC Address Table Size	1K entries
Features	Flow control, full duplex capability, power over Ethernet (PoE), auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3af, IEEE 802.3x
Dimensions (WxDxH)	17.1 cm x 9.8 cm x 2.7 cm

Extended details

General

Device Type	Switch - 8 ports
Enclosure Type	Desktop
Subtype	Fast Ethernet
Ports	4 x 10/100 (PoE) + 4 x 10/100
Power Over Ethernet (PoE)	PoE
MAC Address Table Size	1K entries
Features	Flow control, full duplex capability, power over Ethernet (PoE), auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3af, IEEE 802.3x
Status Indicators	Port transmission speed, power, link/activity
	Expansion / Connectivity
Interfaces	4 x 100Base-TX RJ-45 ¦ 4 x 100Base-TX RJ-45 PoE
	Power
Power Device	External power adapter
	Miscellaneous
Compliant Standards	FCC
	Dimensions & Weight
Width	17.1 cm
Depth	9.8 cm
Height	2.7 cm
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90%

Technical data © CNET Content Solutions. Subject to technical modifications and errors.