



TP-LINK Archer T3U Plus - Network adapter

USB 3.0 - 802.11ac

Group	Network Equipment
Manufacturer	TP-LINK
Manufacturer item no.	ARCHER T3U PLUS
EAN/UPC	6935364053413

Description

AC1300 (867 Mbps on the 5 GHz band or 400 Mbps on the 2.4 GHz band) dual-band Wi-Fi to ensure all your devices run at full speed. Improves the throughput and efficiency of the whole network with MU-MIMO technology. The 2.4 GHz and 5 GHz bands provide flexible connectivity, giving your devices access to the latest dual-band Wi-Fi router for faster speed and extended range. Advanced external high-gain antennas greatly enhance the reception and transmission signal strength of the USB adapter.

Main features

Product Description	TP-Link Archer T3U Plus - network adapter - USB 3.0
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	SuperSpeed USB 3.0
Dimensions (WxDxH)	5.78 cm x 1.8 cm x 17.34 cm
Data Link Protocol	802.11ac
Performance	Maximum data rate (2.4 GHz): 400 Mbps Maximum data rate (5 GHz): 867 Mbps
Frequency Band	2.4 GHz, 5 GHz
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
System Requirements	Microsoft Windows XP/ 7 / 8 / 8.1 / 10

Extended details

General	
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	SuperSpeed USB 3.0
Networking	
Connectivity Technology	Wireless
Data Link Protocol	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac



Performance	Maximum data rate (2.4 GHz): 400 Mbps Maximum data rate (5 GHz): 867 Mbps
Frequency Band	2.4 GHz, 5 GHz
Status Indicators	Status
Features	MU-MIMO technology
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
Miscellaneous	
Encryption Algorithm	WPA, WPA2, WPA-PSK, WPA2-PSK, WEP
Compliant Standards	FCC, RoHS
Software / System Requirements	
Software Included	Drivers & Utilities
OS Required	Microsoft Windows XP/ 7 / 8 / 8.1 / 10
Dimensions & Weight	
Width	5.78 cm
Depth	1.8 cm
Height	17.34 cm
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.