

ViewSonic VA2215-H - LED monitor

22" (21.5" viewable) - 1920 x 1080 Full HD (1080p) @ 75 Hz - VA - 250 cd/m² - 3000:1 - 5 ms - HDMI - VGA

Group	Flat Screens
Manufacturer	ViewSonic
Manufacturer item no.	VA2215-H
EAN/UPC	0766907014150



Description

The ViewSonic VA2215-H is a 22" Full HD monitor with HDMI and VGA input for business or home usage. Delivering a stunning image quality with low power consumption, this monitor provides six ViewMode presets that deliver optimized screen performance based on your needs. Adaptive sync means no tearing or stuttering even when gaming. The eye care technology that comes standard with all VA monitors helps to eliminate eyestrain from extended viewing periods. A VESA-compatible mount makes this monitor is easy to setup on the wall or with a wide range of industry-standard mounts.

Main features

Product Description	ViewSonic VA2215-H - LED monitor - Full HD (1080p) - 22"
Device Type	LED-backlit LCD monitor - 22"
Energy Class	Class F
Power Consumption (On mode)	17 W
Adaptive-Sync Technology	AMD FreeSync
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.241 mm
Brightness	250 cd/m²
Contrast Ratio	3000:1 / 50000000:1 (dynamic)
Response Time	5 ms (grey-to-grey)
Colour Support	16.7 million colours (8-bit)
Colour Gamut	104% sRGB, 72% NTSC
Input Connectors	HDMI, VGA
Display Position Adjustments	Tilt
Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - with stand	49.2 cm x 18.8 cm x 37.7 cm
Weight	2.4 kg
Environmental Standards	ENERGY STAR Qualified EPEAT Silver

Compliant Standards

FCC Class B certified, BSMI, ICES-003, NOM, CB, DDC/CI, RoHS, WEEE, cTUVus, REACH, CEC, UkrSEPRO, ERP, EAC, CE/EMC, VESA TMDS, Mexico Energy label, UKCA

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class F
Diagonal Size	22"
Viewable Size	21.5"
Adaptive-Sync Technology	AMD FreeSync
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.241 mm
Brightness	250 cd/m ²
Contrast Ratio	3000:1 / 50000000:1 (dynamic)
Colour Support	16.7 million colours (8-bit)
Colour Gamut	104% sRGB, 72% NTSC
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	24 - 86 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Backlight Technology	LED backlight
OSD Languages	Czech, Chinese (traditional), Chinese (simplified), English, German, French, Italian, Finnish, Swedish, Russian, Spanish, Turkish, Japanese, Korean
Features	SuperClear, Eco-Mode, game mode, Flicker Free technology, Transition Minimised Differential Signaling (TMDS) technology, Blue Light Filter technology, Movie Mode, text mode, web mode, mono mode, ViewMode, Eye-Care Technology
Dimensions (WxDxH)	49.2 cm x 18.8 cm x 37.7 cm - with stand
Weight	2.4 kg
	Connectivity
Interfaces	VGA HDMI Audio line-out (mini-jack)
	Mechanical
Display Position Adjustments	Tilt
Tilt Angle	-5/+20
VESA Mounting Interface	75 x 75 mm
	Miscellaneous

Features	Security lock slot (cable lock sold separately), detachable stand, VESA interface support
Cables Included	1 x HDMI cable
Backlight Life	30,000 hours
Compliant Standards	FCC Class B certified, BSMI, ICES-003, NOM, CB, DDC/CI, RoHS, WEEE, cTUVus, REACH, CEC, UkrSEPRO, ERP, EAC, CE/EMC, VESA TMDS, Mexico Energy label, UKCA
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	17 W
Power Consumption SDR (On mode)	17 kWh/1000h
Power Consumption (Typical)	16 Watt
Power Consumption (Max)	22 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.3 Watt
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 49.2 cm - depth: 18.8 cm - height: 37.7 cm - weight: 2.4 kg Without stand - width: 49.2 cm - depth: 3.8 cm - height: 28.2 cm - weight: 2 kg
Dimensions & Weight (Shipping)	
Shipping Width	57 cm
Shipping Depth	11.8 cm
Shipping Height	38.3 cm
Shipping Weight	3.5 kg
Sustainability Information	
EPEAT Compliant	EPEAT Silver
ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years - pick-up and return
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.