

ViewSonic VG2408A-MHD - LED monitor

24" (23.8" viewable) - 1920 x 1080 Full HD (1080p) @ 100 Hz - IPS - 250 cd/m² - 1300:1 - 5 ms - HDMI - VGA - DisplayPort - speakers

Group	Flat Screens
Manufacturer	ViewSonic
Manufacturer item no.	VG2408A-MHD
EAN/UPC	0766907024128



Description

ViewSonic VG2408A-MHD - LED monitor - 24" (23.8" viewable) - 1920 x 1080 Full HD (1080p) @ 100 Hz - IPS - 250 cd/m² - 1300:1 - 5 ms - HDMI, VGA, DisplayPort - speakers

Main features

Product Description	ViewSonic VG2408A-MHD - LED monitor - Full HD (1080p) - 24"
Device Type	LED-backlit LCD monitor - 24"
Energy Class	Class E
Power Consumption (On mode)	17 W
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 (DisplayPort: 100 Hz, HDMI: 100 Hz, VGA: 75 Hz)
Pixel Pitch	0.275 mm
Brightness	250 cd/m ²
Contrast Ratio	1300:1 / 50000000:1 (dynamic)
Response Time	5 ms (grey-to-grey), 5 ms (grey-to-grey with overdrive)
Colour Support	16.7 million colours
Colour Gamut	108% sRGB, 77% NTSC, 99% sRGB
Input Connectors	HDMI, VGA, DisplayPort
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 100-240 V
Dimensions (WxDxH) - with stand	54.2 cm x 22.3 cm x 38.62 cm
Weight	5.2 kg
Environmental Standards	ENERGY STAR Qualified
Compliant Standards	CB, RoHS, WEEE, REACH, UkrSEPRO, ERP, EAC, UKCA, TCO Certified 9.0

Extended details

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	24"
Viewable Size	23.8"
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 (DisplayPort: 100 Hz, HDMI: 100 Hz, VGA: 75 Hz)
Pixel Pitch	0.275 mm
Brightness	250 cd/m ²
Contrast Ratio	1300:1 / 50000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	108% sRGB, 77% NTSC, 99% sRGB
Response Time	5 ms (grey-to-grey), 5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate	38 - 100 Hz
Horizontal Refresh Rate	24 - 115 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	SuperClear, Eco-Mode, Flicker Free technology, Eye-Care+ Technology, Variable refresh rate (VRR), Eye ProTech+ technology
Dimensions (WxDxH)	54.2 cm x 22.3 cm x 38.62 cm - with stand
Weight	5.2 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	2 Watt
Connectivity	
Interfaces	DisplayPort HDMI VGA Audio line-out
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-4/28
Swivel Angle	360
Rotation Angle	180
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm, VESA
Miscellaneous	
Features	Security lock slot (cable lock sold separately)

Cables Included	1 x HDMI cable
Backlight Life	30,000 hours
Compliant Standards	CB, RoHS, WEEE, REACH, UkrSEPRO, ERP, EAC, UKCA, TCO Certified 9.0
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V
Power Consumption (On mode)	17 W
Power Consumption SDR (On mode)	17 kWh/1000h
Power Consumption (Typical)	16 Watt
Power Consumption (Max)	18 Watt
Power Consumption Stand by	0.3 Watt
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 54.2 cm - depth: 4.4 cm - height: 32.3 cm - weight: 3.2 kg With stand - width: 54.2 cm - depth: 22.3 cm - height: 38.62 cm - weight: 5.2 kg
Dimensions & Weight (Shipping)	
Shipping Width	60.9 cm
Shipping Depth	39.8 cm
Shipping Height	17.2 cm
Shipping Weight	6.8 kg
Sustainability Information	
ENERGY STAR Certified	Yes
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.