

ViewSonic VG2708A-MHD - LED monitor

27" - 1920 x 1080 Full HD (1080p) @ 100 Hz - IPS - 250 cd/m² - 1300:1 - 5 ms - HDMI - VGA - DisplayPort - speakers

Group	Flat Screens
Manufacturer	ViewSonic
Manufacturer item no.	VG2708A-MHD
EAN/UPC	0766907024159



Description

ViewSonic VG2708A-MHD - LED monitor - 27" - 1920 x 1080 Full HD (1080p) @ 100 Hz - IPS - 250 cd/m² - 1300:1 - 5 ms - HDMI, VGA, DisplayPort - speakers

Main features

Product Description	ViewSonic VG2708A-MHD - LED monitor - Full HD (1080p) - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class E
Power Consumption (On mode)	21 W
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 (DisplayPort: 100 Hz, HDMI: 100 Hz, VGA: 75 Hz)
Pixel Pitch	0.311 mm
Brightness	250 cd/m²
Contrast Ratio	1300:1 / 50000000:1 (dynamic)
Response Time	5 ms (grey-to-grey), 5 ms (grey-to-grey with overdrive)
Colour Support	16.7 million colours
Colour Gamut	108% sRGB, 77% NTSC, 99% sRGB
Input Connectors	HDMI, VGA, DisplayPort
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 100-240 V
Dimensions (WxDxH) - with stand	61.5 cm x 22.3 cm x 40.738 cm
Weight	6.1 kg
Environmental Standards	ENERGY STAR Qualified
Compliant Standards	CB, RoHS, WEEE, REACH, UkrSEPRO, ERP, EAC, UKCA, TCO Certified 9.0

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	27"
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 (DisplayPort: 100 Hz, HDMI: 100 Hz, VGA: 75 Hz)
Pixel Pitch	0.311 mm
Brightness	250 cd/m²
Contrast Ratio	1300:1 / 50000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	108% sRGB, 77% NTSC, 99% sRGB
Response Time	5 ms (grey-to-grey), 5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate	38 - 100 Hz
Horizontal Refresh Rate	24 - 115 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	SuperClear, Eco-Mode, Flicker Free technology, Eye-Care+ Technology, Variable refresh rate (VRR)
Dimensions (WxDxH)	61.5 cm x 22.3 cm x 40.738 cm - with stand
Weight	6.1 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Connectivity
Interfaces	DisplayPort HDMI VGA Audio line-out
	Mechanical
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-4/28
Swivel Angle	360
Rotation Angle	180
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm, VESA
	Miscellaneous
Features	Security lock slot (cable lock sold separately), detachable stand

Cables Included	1 x HDMI cable
Backlight Life	30,000 hours
Compliant Standards	CB, RoHS, WEEE, REACH, UkrSEPRO, ERP, EAC, UKCA, TCO Certified 9.0
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V
Power Consumption (On mode)	21 W
Power Consumption SDR (On mode)	21 kWh/1000h
Power Consumption (Typical)	19 Watt
Power Consumption (Max)	21 Watt
Power Consumption Stand by	0.3 Watt
Software / System Requirements	
OS Required	Apple MacOS, Microsoft Windows 10 / 11
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 61.5 cm - depth: 4.6 cm - height: 36.4 cm - weight: 4.1 kg With stand - width: 61.5 cm - depth: 22.3 cm - height: 40.738 cm - weight: 6.1 kg
Dimensions & Weight (Shipping)	
Shipping Width	67.9 cm
Shipping Depth	16.7 cm
Shipping Height	45.6 cm
Shipping Weight	7.7 kg
Sustainability Information	
ENERGY STAR Certified	Yes
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.