

Xerox Phaser 6510V/DNI - Printer

colour - Duplex - LED - A4/Legal - 1200 x 2400 dpi - up to 28 ppm (mono) / up to 28 ppm (colour) - capacity: 300 sheets - Gigabit LAN - Wi-Fi(n) - USB 3.0 - Sold

Group	Printers
Manufacturer	Xerox
Manufacturer item no.	6510V_DNI
EAN/UPC	0095205835519



Description

Xerox Phaser 6510V/DNI - Printer - colour - Duplex - LED - A4/Legal - 1200 x 2400 dpi - up to 28 ppm (mono) / up to 28 ppm (colour) - capacity: 300 sheets - Gigabit LAN, Wi-Fi(n), USB 3.0 - Sold

Main features

Product Description	Xerox Phaser 6510V/DNI - printer - colour - LED
Printer Type	Workgroup printer - LED - colour
Weight	23.8 kg
Media Size Class	A4/Legal
Max Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm)
Min Media Size (Custom)	76 mm x 127 mm
Max Media Size (Custom)	216 mm x 356 mm
Print Speed	Up to 30 ppm - B/W - ANSI A (Letter) (216 x 279 mm) ¦ Up to 30 ppm - colour - ANSI A (Letter) (216 x 279 mm) ¦ Up to 28 ppm - B/W - A4 (210 x 297 mm) ¦ Up to 28 ppm - colour - A4 (210 x 297 mm)
Max Resolution (B&W)	1200 x 2400 dpi
Max Resolution (Colour)	1200 x 2400 dpi
Automatic Duplexing	Yes
Interface	Gigabit LAN, Wi-Fi(n), USB 3.0
AirPrint Enabled	Yes
Processor	733 MHz
RAM Installed (Max)	1 GB
Language Simulation	PCL 5E, PostScript 3, PCL 6, PDF, TIFF
Media Type	Envelopes, labels, plain paper, bond paper, recycled paper, card stock, punched paper, preprinted paper

Total Media Capacity	300 sheets
Media Handling	250-sheet input tray, 50-sheet bypass tray
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	3000 pages
Networking	Print server
Power	AC 240 V
System Requirements	Linux, Microsoft Windows 2000 Server, SuSe Linux, HP-UX 11i v2, Microsoft Windows Server 2003, Red Hat Enterprise Linux, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2008, Oracle Solaris 10, IBM AIX 5, Microsoft Windows Server 2012, Red Hat Fedora Core 12 - 15, Oracle Solaris 9, Apple MacOS X 10.9 or later, Microsoft Windows 7 / 8 / 10
Pricing Type	Sold
Dimensions (WxDxH)	42 cm x 48.3 cm x 34.7 cm

Extended details

	General
Printer Type	Workgroup printer - LED - colour
	Printer
Print Speed	Up to 30 ppm - B/W - ANSI A (Letter) (216 x 279 mm) ¦ Up to 30 ppm - colour - ANSI A (Letter) (216 x 279 mm) ¦ Up to 28 ppm - B/W - A4 (210 x 297 mm) ¦ Up to 28 ppm - colour - A4 (210 x 297 mm)
Connectivity Technology	Wired
Interface	Gigabit LAN, Wi-Fi(n), USB 3.0
AirPrint Enabled	Yes
Max Resolution (B&W)	1200 x 2400 dpi
Max Resolution (Colour)	1200 x 2400 dpi
Automatic Duplexing	Yes
PostScript Support	Standard
First Print Out Time B/W	7.5 sec
First Print Out Time Colour	8.8 sec
Language Simulation	PCL 5E, PostScript 3, PCL 6, PDF, TIFF
Fonts Included	136 x PostScript ¦ 88 x PCL
Media Handling	250-sheet input tray, 50-sheet bypass tray
	Processor
Processor	733 MHz
	RAM
RAM Installed (Max)	1 GB

	Media Handling
Media Type	Envelopes, labels, plain paper, bond paper, recycled paper, card stock, punched paper, preprinted paper
Media Size Class	A4/Legal
Max Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm)
Min Media Size (Custom)	76 mm x 127 mm
Max Media Size (Custom)	216 mm x 356 mm
Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), A4 (210 x 297 mm)
Media Weight	60 g/m ² - 220 g/m ²
Total Media Capacity	300 sheets
Media Feeders	1 x automatic - 250 sheets - Legal (216 x 356 mm) weight: 60 g/m ² - 220 g/m ² 1 x automatic - 50 sheets - Legal (216 x 356 mm) weight: 60 g/m ² - 220 g/m ²
Max Media Capacity	850 sheets
Output Trays Capacity	150 sheets
	Duty Cycle
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	3000 pages
	Networking
Networking	Print server
Remote Management Protocol	SNMP 3, IPP, HTTP, HTTPS
Security Protocols & Features	LDAP, Apple Bonjour, TLS, IPsec, 802.1x, IP filtering, Wi-Fi Direct
	Expansion / Connectivity
Connections	1 x USB 3.0 - 9 pin USB Type B 1 x Gigabit LAN - RJ-45
	Miscellaneous
Compliant Standards	GS, NOM, ICES, cTUVus, UkrSEPRO, EAC, NMB-3 Class A, BIS
Pricing Type	Sold
	Power
Power Device	Power supply - internal
Voltage Required	AC 240 V
Frequency Required	50 Hz
Power Consumption Operational	350 Watt
Power Consumption Stand by	44 Watt
Power Consumption Sleep	1 Watt
	Software / System Requirements

OS Required	Linux, Microsoft Windows 2000 Server, SuSe Linux, HP-UX 11i v2, Microsoft Windows Server 2003, Red Hat Enterprise Linux, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2008, Oracle Solaris 10, IBM AIX 5, Microsoft Windows Server 2012, Red Hat Fedora Core 12 - 15, Oracle Solaris 9, Apple MacOS X 10.9 or later, Microsoft Windows 7 / 8 / 10
Environmental Standards	
ENERGY STAR	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - 1 year - on-site
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	32 °C
Humidity Range Operating	15 - 85%
Sound Emission (Idle)	24.9 dBA
Sound Emission (Operating)	51.9 dBA
Dimensions & Weight	
Width	42 cm
Depth	48.3 cm
Height	34.7 cm
Weight	23.8 kg
Dimensions & Weight (Shipping)	
Width (Shipping)	58 cm
Depth (Shipping)	63.4 cm
Height (Shipping)	50.5 cm

Technical data © 1WorldSync. Subject to technical modifications and errors.