

Xerox VersaLink C7000V/N - Printer

colour - laser - A3 - 1200 x 2400 dpi - up to 35 ppm (mono) / up to 35 ppm (colour) - capacity: 620 sheets - Gigabit LAN - NFC - USB 3.0

Group	Printers
Manufacturer	Xerox
Manufacturer item no.	C7000V_N
EAN/UPC	0095205845693



Description

When you need your work to stand out from the rest, count on the VersaLink C7000 color printer - featuring Xerox ConnectKey technology. Ready for the way you want to work, the C7000 is mobile-ready, app-enabled and ready to customize. Meet your challenges head-on with the VersaLink C7000 - your modern workplace assistant

Main features

Product Description	Xerox VersaLink C7000V/N - printer - colour - laser
Printer Type	Workgroup printer - laser - colour
Weight	54.3 kg
Media Size Class	A3
Max Media Size	297 x 432 mm
Min Media Size (Custom)	88.9 mm x 98.4 mm
Max Media Size (Custom)	297 mm x 432 mm
Print Speed	Up to 35 ppm - colour Up to 35 ppm - B/W
Max Resolution (B&W)	1200 x 2400 dpi
Automatic Duplexing	Optional
Interface	Gigabit LAN, NFC, USB 3.0
AirPrint Enabled	Yes
Preview Screen Size	5"
Processor	1.05 GHz
RAM Installed (Max)	2 GB (2 GB)
Language Simulation	PCL 5E, PostScript 3, PCL 6, HP GL, PDF, XPS, TIFF, JPEG
Media Type	Envelopes, plain paper
Total Media Capacity	620 sheets
Media Handling	520-sheet input tray, 100-sheet bypass tray
Monthly Duty Cycle (max)	153000 pages
Recommended Monthly Volume	10000 pages
Networking	Print server

System Requirements	Linux, Microsoft Windows Server 2003, Red Hat Enterprise Linux, Microsoft Windows 7, HP-UX 11i v3, Microsoft Windows Server 2008, Windows 8, Microsoft Windows Server 2012, Apple MacOS X 10.10, Windows 10, Apple MacOS X 10.11, Oracle Solaris 11.3, IBM AIX 7.2, Red Hat Fedora Core 24, SUSE Linux 13.2, Apple macOS 10.12
Dimensions (WxDxH)	59 cm x 67.08 cm x 63.7 cm

Extended details

	General
Printer Type	Workgroup printer - laser - colour
	Printer
Print Speed	Up to 35 ppm - colour Up to 35 ppm - B/W
Built-in Devices	5 inch LCD touch screen
Preview Screen Size	5"
Connectivity Technology	Wired
Interface	Gigabit LAN, NFC, USB 3.0
AirPrint Enabled	Yes
Max Resolution (B&W)	1200 x 2400 dpi
Automatic Duplexing	Optional
PostScript Support	Standard
First Print Out Time B/W	5.1 sec
First Print Out Time Colour	7.6 sec
Language Simulation	PCL 5E, PostScript 3, PCL 6, HP GL, PDF, XPS, TIFF, JPEG
Fonts Included	136 x PostScript 83 x PCL
Media Handling	520-sheet input tray, 100-sheet bypass tray
	Processor
Processor	1.05 GHz
	RAM
RAM Installed (Max)	2 GB / 2 GB (max)
	Media Handling
Media Type	Envelopes, plain paper
Media Size Class	A3
Max Media Size	297 x 432 mm
Min Media Size (Custom)	88.9 mm x 98.4 mm
Max Media Size (Custom)	297 mm x 432 mm
Media Sizes	297 x 432 mm, 139.7 x 182 mm, 88.9 x 98.4 mm
Envelope Sizes	International DL (110 x 220 mm), Com-10 (105 x 241 mm), International C5 (162 x 229 mm), Monarch (98.4 x 190.5 mm)
Total Media Capacity	620 sheets
Media Feeders	Input tray: 1 x automatic - 500 sheets - 297 x 432 mm Bypass tray: 1 x automatic - 100 sheets - 297 x 432 mm

Max Media Capacity	2180 sheets
Output Trays Capacity	500 sheets
	Duty Cycle
Monthly Duty Cycle (max)	153000 pages
Recommended Monthly Volume	10000 pages
	Networking
Networking	Print server
Remote Management Protocol	SNMP 3, HTTPS
Security Protocols & Features	Secure Print, SSL, Apple Bonjour, TLS, IPsec
	Expansion / Connectivity
Connections	1 x USB 3.0 1 x Gigabit LAN - RJ-45
	Miscellaneous
Compliant Standards	WHQL, FIPS 140-2, IPv6 Ready, EcoLogo, MEDITECH
	Power
Power Device	Power supply - internal
Power Consumption Operational	1600 Watt
Power Consumption Stand by	94 Watt
Power Consumption Sleep	1 Watt
	Software / System Requirements
OS Required	Linux, Microsoft Windows Server 2003, Red Hat Enterprise Linux, Microsoft Windows 7, HP-UX 11i v3, Microsoft Windows Server 2008, Windows 8, Microsoft Windows Server 2012, Apple MacOS X 10.10, Windows 10, Apple MacOS X 10.11, Oracle Solaris 11.3, IBM AIX 7.2, Red Hat Fedora Core 24, SUSE Linux 13.2, Apple macOS 10.12
	Environmental Standards
Blue Angel	Yes
ENERGY STAR	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 1 year - on-site
	Environmental Parameters
Min Operating Temperature	10 °C
Max Operating Temperature	32 °C
Humidity Range Operating	10 - 85% (non-condensing)
	Dimensions & Weight
Width	59 cm
Depth	67.08 cm
Height	63.7 cm
Weight	54.3 kg
	Dimensions & Weight (Shipping)
Width (Shipping)	71 cm

Depth (Shipping)	77 cm
Height (Shipping)	94.5 cm
Weight (Shipping)	72 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.