

Zebra DS3678-ER - Barcode scanner

portable - 2D imager - decoded - keyboard wedge - RS-232 - USB - Bluetooth 4.0

Group	Scanners
Manufacturer	Zebra
Manufacturer item no.	DS3678-ER3U42A2SVW
EAN/UPC	8596375044951



Description

The practically indestructible DS3678-ER cordless scanners are ready for one of the world's toughest environments - the warehouse. Designed to capture any 1D or 2D barcode from near contact to as far as 70 ft./21.4 m away, these scanners provide the ultimate in versatility - workers can capture large picklist codes and small codes at near contact as easily as barcodes on pallets and location codes on the top of your warehouse racks. And truly unstoppable performance helps you drive throughput, accuracy and customer service to a great level.

Main features

Product Description	Zebra DS3678-ER - barcode scanner
Type	Barcode scanner - portable - keyboard wedge, RS-232, USB, Bluetooth 4.0 - decoded
Colour	Industrial green
Minimum Bar Width	3 mil
Scan Element Type	2D imager
Connectivity Technology	Wireless, wired
Wireless Connectivity	Bluetooth 4.0 LE
Battery	1 x Lithium Ion
Dimensions (WxDxH)	7.7 cm x 14.3 cm x 18.5 cm
Weight	436 g

Extended details

	General
Type	Barcode scanner - portable
Colour	Industrial green
	Barcode
Interface Type	Keyboard wedge, RS-232, USB, Bluetooth 4.0
Minimum Bar Width	3 mil
Scan Element Type	2D imager
Scan Mode	Single-pass
Skew (Degrees)	60
Pitch (Degrees)	60

Decode Capability	GS1 DataBar, QR code, MaxiCode, Aztec code, MicroPDF417, PDF417, Data Matrix, TLC39, Micro QR code, China Han Xin Code
TTL Decoding	Decoded
Connectivity Technology	Wireless, wired
OK Notification	Beeper, LED indicator, vibration
Features	Rugged
	Networking
Wireless Connectivity	Bluetooth 4.0 LE
	Expansion / Connectivity
Interfaces	1 x USB 1 x keyboard wedge 1 x RS-232
	Miscellaneous
Included Accessories	Cradle
Cables Included	1 x USB cable - external
Compliant Standards	UL, VDE, EN 61000-6-2, RoHS, UL 60950-1 Second Edition, IP67, CAN/CSA C22.2 No. 60950-1-07, EN 61000-3-2:2006+A1:2009+A2:2009, IEC 60601-1-2:2007, EN 50581:2012, ICES-003 issue 5 Class B, IEC 62471:2006, EN 62471:2008, EN 60601-1-2:2007, EN 60950-1:2006+A11:2009+A1:2010+A12:2011+AC:2011, EN 61000-3-3:2013, EN 55024:2010, EN 55022:2010/AC:2011, IEC 60950-1:2005 + A1:2009 + A2:2013, CU, FCC CFR47 Part 15 B Class B
	Power
Power Device	Power adapter
Battery	1 x Lithium Ion
	Dimensions & Weight
Width	7.7 cm
Depth	14.3 cm
Height	18.5 cm
Weight	436 g
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	-20 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 95% (non-condensing)
Drop Specification	2.4 m to concrete

Technical data © 1WorldSync. Subject to technical modifications and errors.