



## Zebra DS2208 - USB Kit - barcode scanner

handheld - 2D imager - 762 mm / sec - decoded - keyboard wedge - RS-232 - USB

Group	Scanners
Manufacturer	Zebra
Manufacturer item no.	DS2208-SR7U2100AZW

### Description

2D barcodes have made their way to your point of sale, appearing on everything from the items your customers are purchasing to printed and electronic coupons and loyalty cards.

Your 1D scanner can't capture the 2D codes, leading to exceptions that slow down the check-out process and frustrate customers at that key last personal touchpoint in your store.

### Main features

Product Description	Zebra DS2208 - USB Kit - barcode scanner
Type	Barcode scanner - handheld - keyboard wedge, RS-232, USB - decoded
Colour	Twilight black
Minimum Bar Width	4 mil
Scan Element Type	2D imager
Sensor Resolution	640 x 480
Scan Speed	762 mm / sec
Connectivity Technology	Wired
Dimensions (WxDxH)	6.6 cm x 9.9 cm x 16.5 cm
Weight	161.6 g

### Extended details

#### General

Type	Barcode scanner - handheld
Colour	Twilight black

#### Barcode

Interface Type	Keyboard wedge, RS-232, USB
Minimum Bar Width	4 mil
Scan Element Type	2D imager
Sensor Resolution	640 x 480
Light Source Wave Length	624 nm



Scan Mode	Single-pass
Scan Speed	762 mm / sec
Max Working Distance	36.8 cm
Skew (Degrees)	65
Pitch (Degrees)	65
Print Contrast Signal (PCS)	25%
Decode Capability	Code 93, Industrial 2 of 5, Code 39, NW-7, GS1 DataBar, QR code, MaxiCode, Aztec code, Italy Pharmacode, Codabar, Code 128, Code 11, UPC, PDF417, MSI-Plessey, Data Matrix, TLC39, Micro QR code, China Han Xin Code
TTL Decoding	Decoded
Connectivity Technology	Wired
OK Notification	Beeper, LED indicator
<b>Expansion / Connectivity</b>	
Interfaces	1 x USB   1 x RS-232   1 x keyboard wedge
<b>Miscellaneous</b>	
Cables Included	1 x USB cable - external
Compliant Standards	UL, VDE, EN 61000-6-2, RoHS, UL 60950-1 Second Edition, CAN/CSA C22.2 No. 60950-1-07, IP42, EN 61000-3-2:2006+A1:2009+A2:2009, IEC 60601-1-2:2007, EN 50581:2012, ICES-003 issue 5 Class B, IEC 62471:2006, EN 62471:2008, EN 60601-1-2:2007, EN 60950-1:2006+A11:2009+A1:2010+A12:2011+AC:2011, EN 61000-3-3:2013, EN 55024:2010, EN 55022:2010/AC:2011, IEC 60950-1:2005 + A1:2009 + A2:2013, CU, FCC CFR47 Part 15 B Class B
<b>Dimensions &amp; Weight</b>	
Width	6.6 cm
Depth	9.9 cm
Height	16.5 cm
Weight	161.6 g
<b>Manufacturer Warranty</b>	
Service & Support	Limited warranty - 5 years
<b>Environmental Parameters</b>	
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 95% (non-condensing)
Drop Specification	1.5 m to concrete

Technical data © CNET Content Solutions. Subject to technical modifications and errors.