



Zebra Symbol DS4308-SR - Barcode scanner

handheld - 2D imager - decoded - USB

Group	Scanners
Manufacturer	Zebra
Manufacturer item no.	DS4308-SR7U2100SGW

Description

The DS4308 is a feature-rich 2D imager that resets the bar for scanning performance, scanning range, versatility and ease- of-use. Workers can capture virtually any bar code faster than ever, whether it is displayed on a smartphone, tablet or computer or printed on a label - even if it is scratched, damaged or dirty. Its small and lightweight design offers the ergonomics your workers need for all day comfort in the most scan intensive jobs. The Standard Range (SR) model offers an extraordinary range, eliminating the need to purchase separate standard and extended range scanners.

Main features

Product Description	Symbol DS4308-SR - barcode scanner
Type	Barcode scanner - handheld - USB - decoded
Colour	Twilight black
Minimum Bar Width	4 mil
Scan Element Type	2D imager
Connectivity Technology	Wired
Dimensions (WxDxH)	6.7 cm x 9.8 cm x 16.5 cm
Weight	162 g

Extended details

General	
Type	Barcode scanner - handheld
Colour	Twilight black
Barcode	
Interface Type	USB
Minimum Bar Width	4 mil
Scan Element Type	2D imager
Light Source Wave Length	617 nm
Max Working Distance	41.1 cm

Skew (Degrees)	60
Pitch (Degrees)	65
Print Contrast Signal (PCS)	20%
Decode Capability	EAN/JAN, Code 93, Matrix 2 of 5, Code 39, UCC/EAN-128, ISBT 128, GS1 DataBar, QR code, MaxiCode, Aztec code, Bookland, Code 32, Code 39 Full ASCII, Discrete 2 of 5, MicroPDF417, Codabar, Code 128, Code 11, UPC, Interleaved 2 of 5, Postnet, PDF417, MSI-Plessey, Data Matrix, PLANET, TLC39, Australian Post, Canadian Post, China Post, Japanese Post, Kix (Netherlands) Post, Korea Post, EAN-UCC Composite, ISSN, Code 39 Trioptic, UK Post, Royal Mail, Micro QR code, China Han Xin Code
TTL Decoding	Decoded
Connectivity Technology	Wired
OK Notification	Beeper
Features	PRZM Intelligent Imaging technology
Expansion / Connectivity	
Interfaces	1 x USB
Miscellaneous	
Included Accessories	Stand
Cables Included	1 x USB cable - external
Compliant Standards	EN55024, EN55022 Class B, ICES-003 Class B, FCC Part 15 B, UL 60950-1 Second Edition, EN 60601-1-2, CSA C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, RoHS 2011/65/EU, IEC 62471:2006, EN 62471:2008
Dimensions & Weight	
Width	6.7 cm
Depth	9.8 cm
Height	16.5 cm
Weight	162 g
Manufacturer Warranty	
Service & Support	Limited warranty - 5 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 95% (non-condensing)
Drop Specification	1.8 m to concrete