



Zebra DS9208 Omnidirectional Hands-Free Presentation Imager

Barcode scanner - desktop - 2D imager - 2300 mm / sec - decoded - USB

Group	Scanners
Manufacturer	Zebra
Manufacturer item no.	DS9208-SR4NNU21ZE
EAN/UPC	5054484350255

Description

Whether you need to scan printed bar codes on paper labels or mobile bar codes on the screen of a mobile phone, with the Zebra DS9208, you'll be ready. You get the versatility to scan any 1D or 2D bar code - from the printed labels in retail that identify product and pricing at the register to mobile coupons, mobile gift and loyalty cards, boarding passes and even theater tickets. And the DS9208 provides all the features you need to keep your workers productive: industry-leading scanning speed; true point-and-shoot scanning simplicity - no need to align bar code and scanner; and hands-free and handheld flexibility.

Main features

Product Description	Zebra DS9208 Omnidirectional Hands-Free Presentation Imager - barcode scanner
Type	Barcode scanner - desktop - USB - decoded
Colour	Midnight black
Localisation	EMEA
Minimum Bar Width	4 mil
Scan Element Type	2D imager
Scan Speed	2300 mm / sec
Connectivity Technology	Wired
Dimensions (WxDxH)	8.2 cm x 8 cm x 14 cm
Weight	284 g

Extended details

General	
Type	Barcode scanner - desktop
Colour	Midnight black
Localisation	EMEA
Barcode	



Interface Type	USB
Minimum Bar Width	4 mil
Scan Element Type	2D imager
Light Source Wave Length	630 nm
Scan Mode	Single-pass
Scan Speed	2300 mm / sec
Max Working Distance	26.7 cm
Skew (Degrees)	60
Pitch (Degrees)	65
Decode Capability	Code 93, Matrix 2 of 5, Code 39, UCC/EAN-128, ISBT 128, NW-7, ISBN, GS1 DataBar, QR code, MaxiCode, Aztec code, Bookland, Code 32, Code 39 Full ASCII, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Discrete 2 of 5, MicroPDF417, Italy Pharmacode, Codabar, Code 128, Code 11, UPC, Interleaved 2 of 5, Postnet, PDF417, MSI-Plessey, Data Matrix, PLANET, TLC39, Australian Post, Japanese Post, Kix (Netherlands) Post, IATA 2 of 5, UPC-E1, UPC-A/EAN-13 with Extended Coupon Code, EAN-UCC Composite, MacroPDF417, ISSN, Code 128 Full ASCII, Code 39 Trioptic, UK Post, Royal Mail, Micro QR code, 4-State postal code, CC-A, CC-B, CC-C, GS1 DataBar Omnidirectional, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked, GS1 DataBar Limited
TTL Decoding	Decoded
Connectivity Technology	Wired
OK Notification	Beeper, LED indicator
Features	Reduced Space Symbolology (RSS)
Miscellaneous	
Cables Included	1 x USB cable
Compliant Standards	VCCI, EN55022, EN55024, CISPR 22, ICES-003 Class B, RoHS, Laser Class 2, UL 60950-1, IEC 60950-1, EN 60950-1, IEC 60825-1, FCC CFR47 Part 15 B, IEC 60529 IP50, CSA C22.2 No. 60950-1, EN 60825-1
Software	
Software Included	Drivers & Utilities
Dimensions & Weight	
Width	8.2 cm
Depth	8 cm
Height	14 cm
Weight	284 g
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 85% (non-condensing)
Drop Specification	1.5 m to concrete