



Zebra TLP 2824 Plus - Label printer

thermal transfer - Roll (6 cm) - 203 dpi - up to 102 mm/sec - USB - serial

Group	Printers
Manufacturer	Zebra
Manufacturer item no.	282P-101120-000
EAN/UPC	5052217010797

Description

At 2.2", the direct thermal and thermal transfer TLP 2824 bar code label printer is ideal for retail and other label applications. The TLP 2824 redefines the compact printer class. It fits into areas other printers cannot, withstanding rough handling and integrating easily into a wide range of applications. A 5" media roll capacity and clear media window optimize productivity, while a maximum print speed of 4" per second enables fast job processing.

The TLP 2824 excels in delivering printing solutions for business and professional offices, including retail point of sale, shelf labeling, product marking, healthcare specimen labeling and patient tracking, inventory and asset management, small office or home office mailing, shipping, and file folder labeling.

Main features

Product Description	Zebra TLP 2824 Plus - label printer - B/W - thermal transfer
Printer Type	Label printer - thermal transfer - B/W
Weight	1.6 kg
Max Media Size	Roll (6 cm)
Max Media Size (Custom)	60 mm
Print Speed	Up to 102 mm/sec - max speed
Max Resolution (B&W)	203 dpi
Interface	USB, serial
RAM Installed (Max)	8 MB
Flash Memory Installed (Max)	4 MB
Language Simulation	ZPL II, EPL2, EPL
Barcodes	Code 93, Industrial 2 of 5, Code 39, UCC/EAN-128, Code 49, CODABLOCK, GS1 DataBar, QR code, MaxiCode, Aztec code, LOGMARS, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, MicroPDF417, Codabar, Code 128, Code 11, Interleaved 2 of 5, Postnet, PDF417, MSI-Plessey, Data Matrix, Japanese Post, EAN-14, Code 128B, Code 128C, German Post, MSI-3, Code 128A, GS1 DataBar Omnidirectional



Media Type	Labels, continuous forms, perforated thermal paper, receipt paper, fanfold paper, tag stock
Power	AC 120/230 V
Microsoft Certification	Compatible with Windows 7
Dimensions (WxDxH)	13.5 cm x 24.1 cm x 17.8 cm

Extended details

General	
Printer Type	Label printer - thermal transfer - monochrome
Printer	
Print Speed	Up to 102 mm/sec - max speed - 203 dpi
Connectivity Technology	Wired
Interface	USB, serial
Max Resolution (B&W)	203 dpi
Language Simulation	ZPL II, EPL2, EPL
Barcodes	Code 93, Industrial 2 of 5, Code 39, UCC/EAN-128, Code 49, CODABLOCK, GS1 DataBar, QR code, MaxiCode, Aztec code, LOGMARS, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, MicroPDF417, Codabar, Code 128, Code 11, Interleaved 2 of 5, Postnet, PDF417, MSI-Plessey, Data Matrix, Japanese Post, EAN-14, Code 128B, Code 128C, German Post, MSI-3, Code 128A, GS1 DataBar Omnidirectional
RAM	
RAM Installed (Max)	8 MB
Flash Memory	
Flash Memory	4 MB
Media Handling	
Media Type	Labels, continuous forms, perforated thermal paper, receipt paper, fanfold paper, tag stock
Max Media Size	Roll (6 cm)
Max Media Size (Custom)	60 mm
Media Sizes	Roll (6 cm)
Max Printing Width	56 mm
Max Printing Length	991 mm
Media Thickness Range	0.08 mm - 0.18 mm
Roll Maximum Outer Diameter	127 mm
Roll Core Diameter	25.4 mm, 38 mm
Media Feeders	1 x manual - 1 roll - Roll (6 cm)
Expansion / Connectivity	
Connections	1 x RS-232 - 9 pin D-Sub (DB-9) 1 x USB - 4 pin USB Type B
Miscellaneous	
Compatible with Windows 7	"Compatible with Windows 7" software and devices carry Microsoft's assurance that these products have passed tests for compatibility and reliability with 32-bit and 64-bit Windows 7.
Compliant Standards	UL, VCCI, C-Tick, NOM, FCC, IRAM
Power	



Power Device	Power adapter - external
Voltage Required	AC 120/230 V
Frequency Required	50/60 Hz
Software / System Requirements	
Software Included	Drivers & Utilities, ZebraDesigner
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	41 °C
Humidity Range Operating	10 - 90%
Dimensions & Weight	
Width	13.5 cm
Depth	24.1 cm
Height	17.8 cm
Weight	1.6 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.